

Eaton FWA-45A21F

Catalog Number: FWA-45A21F

Eaton Bussmann series FWA high speed fuse, 500 Vac, 500 Vdc, 45A, 100 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWA-45A21F
UPC	
051712795272	
EAN	Product Length/Depth
5027590499279	51 mm
Product Height	Product Width
21 mm	21 mm
Product Weight	Warranty
55.3 g	Not Applicable
Compliances	Certifications
CE Marked	CSA Certified
RoHS Compliant	UL Recognized

Product specifications

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

45 A

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Other

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

21 x 51 mm

Class

Class aR

Clearing (I₂T)

1300 at 150 V

Watt losses

6 W

Fuse shape

Cylindrical

Pre arc (I₂T)

130

Interrupt rating

100 kAIC

Resources

Catalogs

[eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf](#)

Bussmann series complete full line catalog no. 1007

[FWA-45A21F~Eaton Bussmann series high speed cylindrical fuse](#)

Technical data sheets

[720003 FWA](#)

[Connection](#)

Ferrule end x ferrule end

[Construction size](#)

Other

[Material](#)

Ceramic

[Packaging type](#)

Standard

[Voltage rating](#)

150 V

[Fuse type](#)

FWA-A21F



Eaton Corporation plc

Eaton House

30 Pembroke Road
Dublin 4, Ireland

Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](#)