

Eaton FWH-001A6F

Catalog Number: FWH-001A6F

Eaton Bussmann series FWH high speed fuse, 500 Vac (0.25-6.3A), 500 Vdc (2-5A), 1A, 50 kAIC at 0.25-20A, 20 kAIC at 25-30A, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWH-001A6F
UPC	051712796644
EAN	Product Length/Depth
5027590499453	33 mm
Product Height	Product Width
7 mm	7 mm
Product Weight	Warranty
2.8 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	CSA Certified

Product specifications

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

1 A

Breaking capacity

50 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Other

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Class

Class aR

Clearing (I₂T)

2 at 500 V

Watt losses

1.7 W

Response time

>30 min at 150%, <30 min at 200%, <= to 10 sec at 300%

Fuse shape

Cylindrical

Pre arc (I₂T)

0.4

Interrupt rating

50 kAIC

Resources

Catalogs

eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-english.pdf

Bussmann series complete full line catalog no. 1007

Connection

Ferrule end x ferrule end

Construction size

Other

6.3 x 32 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

600 V

Fuse type

FWH-A6F



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)