

Eaton FWP-10B

Catalog Number: FWP-10B

Eaton Bussmann series FWP high speed fuse, 700 Vac (UL), 690 Vac (IEC), 800 Vdc, 10A, 200 kAIC Vac, 50 kAIC at 700 Vdc, None, High speed fuse, Blade end X blade end, Stud



General specifications

| | |
|---|----------------------|
| Product Name | Catalog Number |
| Eaton Bussmann series high speed cylindrical fuse | FWP-10B |
| | UPC |
| | 051712557795 |
| EAN | Product Length/Depth |
| 5027590500142 | 73 mm |
| Product Height | Product Width |
| 15 mm | 15 mm |
| Product Weight | Warranty |
| 24.1 g | Not Applicable |
| Compliances | Certifications |
| CE Marked | CSA Certified |
| RoHS Compliant | UL Recognized |

Product specifications

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

10 A

Breaking capacity

200 kA

Fuse indicator

Non Indicating

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Rated switching capacity

200 A

Rated voltage AC

700 V

Rated voltage DC

700 V

Mounting dimension

M6

Center-to-center distance of connections

63.35 mm

Current type

AC/DC

Class

Class aR

Clearing (I²T)

20 at 700 V

Watt losses

4 W

Resources

Catalogs

[eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

Technical data sheets

[FWP NA bolted fuse-links](#)

Fuse shape

Center bolted tags

Pre arc (I2T)

3.6

Color

None

Interrupt rating

200 kAIC Vac

50 kAIC at 700 Vdc

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating

700 Vac, 700 Vdc (UL)

Fuse type

FWP-B

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia