

# Eaton FWX-2000AH

Catalog Number: FWX-2000AH

Eaton Bussmann series FWX high speed fuse, 600V, 2000A, 200 kAIC Vac, 50 kAIC at 250 Vdc, None, High speed fuse, Blade end X blade end, Flush

## General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWX-2000AH
UPC	
051712795654	
EAN	Product Length/Depth
5027590022002	96 mm
Product Height	Product Width
65 mm	116 mm
Product Weight	Warranty
1951 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	CSA Certified

## Product specifications

### Type

High speed fuse

### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

### Amperage Rating

1 A

### Breaking capacity

200 kA

### Fuse indicator

Non Indicating

### Insulated metal gripping lugs (IMGL)

No

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC/DC

### Rated switching capacity

200 A

### Rated voltage AC

250 V

### Mounting dimension

Other

### Center-to-center distance of connections

65.8 mm

### Current type

AC

### Class

Class aR

### Clearing (I<sub>2</sub>T)

2300000 at 250 V

### Watt losses

151 W

### Fuse shape

Cylindrical, flush end

## Resources

### Catalogs

[eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-english.pdf](http://eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-english.pdf)

Bussmann series complete full line catalog no. 1007

Pre arc (I<sub>2T</sub>)

320000

Color

None

Interrupt rating

200 kAIC Vac

50 kAIC at 250 Vdc

Connection

Blade end x blade end

Construction size

Other

Mounting method

Flush

Packaging type

Standard

Voltage rating

250 Vac, 250 Vdc

Fuse type

FWX-AH

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type B