

Specifications

Eaton FWJ-200A

Catalog Number: FWJ-200A

Eaton Bussmann series FWJ high speed fuse, 700 Vac (UL), 690 Vac (IEC), 800 Vdc (5-50A), 200A, 25 kAIC (35-200A), 100 kAIC (250-2000A), 50 kAIC at 800 Vdc (35-200A, 450-600A), None, High speed fuse, Blade end X blade end, Stud

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWJ-200A
	UPC
	051712796224
EAN	Product Length/Depth
5027590021210	145 mm
Product Height	Product Width
39 mm	39 mm
Product Weight	Warranty
195 g	Not Applicable
Compliances	Certifications
CE Marked	CSA Certified
	UL Recognized

Product specifications

Type	Catalogs
High speed fuse	eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf
Application	Bussmann series complete full line catalog no. 1007
Semiconductor, DC Common bus, DC drives, Power converters/rectifiers	
Amperage Rating	
200 A	
Breaking capacity	
25 kA	
Fuse indicator	
Non Indicating	
Insulated metal gripping lugs (IMGL)	
No	
Utilization category	
aR (accompanied semiconductor protection)	
Voltage type	
AC/DC	
Rated switching capacity	
25 A	
Rated voltage AC	
1000 V	
Rated voltage DC	
800 V	
Mounting dimension	
M10	
Center-to-center distance of connections	
113 mm	
Current type	
AC/DC	
Class	
Class aR	
Clearing (I ₂ T)	
80000 at 1000 V	
Watt losses	
32 W	

Resources

Fuse shape

Center bolted tags

Pre arc (I2T)

11700

Color

None

Interrupt rating

25 kAIC (35-200A)

100 kAIC (250-2000A)

50 kAIC at 800 Vdc (35-200A)

450-600A)

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating

1000 Vac, 800 Vdc

Fuse type

FWJ-A

Fuse system (according to IEC 60269)

Other