

Eaton FWX-1A14F

Catalog Number: FWX-1A14F

Eaton Bussmann series FWX high speed fuse, 600V, 1A, 200 kAIC Vac, 50 kAIC at 250 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWX-1A14F
UPC	
051712795135	
EAN	Product Length/Depth
5027590501354	58 mm
Product Height	Product Width
35 mm	89 mm
Product Weight	Warranty
21.8 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	

Product specifications

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

1600 A

Accessories

CH14 Modular fuse holder

FW14-PCB

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Other

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

14 x 51 mm

Class

Class aR

Watt losses

5.7 W

Fuse shape

Cylindrical

Interrupt rating

200 kAIC

Connection

Resources

Catalogs

[eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-english.pdf](#)

Bussmann series complete full line catalog no. 1007

Technical data sheets

[720006 FWX](#)

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

690 V

Fuse type

FWX-A14F



Eaton Corporation plc

Eaton House

30 Pembroke Road
Dublin 4, Ireland

Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia