

## Specifications

# Eaton FWX-12A14F

Catalog Number: FWX-12A14F

Eaton Bussmann series FWX high speed fuse, 12A, Non Indicating, High speed fuse, Ferrule end X ferrule end

### General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWX-12A14F
	UPC
	051712795562
EAN	Product Length/Depth
5027590501330	55 mm
Product Height	Product Width
32 mm	73 mm
Product Weight	Warranty
21.2 g	Not Applicable
Compliances	
RoHS Compliant	

## Product specifications

### Type

High speed fuse

### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

### Amperage Rating

1200 A

### Accessories

CH14 Modular fuse holder

FW14-PCB

### Breaking capacity

200 kA

### Frequency rating - max

62 Hz

### Frequency rating - min

45 Hz

### Fuse indicator

Other

### Release characteristic

Other

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC

### Fuse size

14 x 51 mm

### Class

Class aR

### Fuse shape

Cylindrical

### Interrupt rating

200 kAIC

### Connection

Ferrule end x ferrule end

### Construction size

## Resources

### Catalogs

[eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-english.pdf](#)

Bussmann series complete full line catalog no. 1007

14 mm x 51 mm

**Material**

Ceramic

**Packaging type**

Standard

**Voltage rating**

700 V

**Fuse type**

FWX-A14F



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia