

# Eaton FWH-6A14F

Catalog Number: FWH-6A14F

Eaton Bussmann series FWH high speed fuse, 6A, 200 kAIC Vac, 50 kAIC at 500 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWH-6A14F
	UPC
	051712557146
EAN	Product Length/Depth
5027590499729	55 mm
Product Height	Product Width
32 mm	73 mm
Product Weight	Warranty
21.2 g	Not Applicable
Compliances	Certifications
CE Marked	CSA Certified
RoHS Compliant	UL Recognized

## Product specifications

### Type

High speed fuse

### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

### Amperage Rating

6 A

### Accessories

CH14 Modular fuse holder  
FW14-PCB

### Breaking capacity

200 kA

### Frequency rating - max

62 Hz

### Frequency rating - min

45 Hz

### Fuse indicator

Non Indicating

### Release characteristic

Other

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC/DC

### Fuse size

14 x 51 mm

### Class

Class aR

### Clearing (I<sub>2</sub>T)

6.4 at 500 V

### Watt losses

1.5 W

### Fuse shape

Cylindrical

### Pre arc (I<sub>2</sub>T)

## Resources

### Catalogs

[eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

### Declarations of conformity

[CE FWC-\\*A10F,FWH-\\*A14F,FWP-\\*A14F,FWP-\\*A14FI etc](#)

[UKCA FWC-\\*A10F,FWH-\\*A14F,FWP-\\*A14F,FWP-\\*A14FI etc](#)

### Technical data sheets

[720008 FWH](#)

1.6

Interrupt rating

50 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

500 V

Fuse type

FWH-A14F



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)