



SITOP PSU6200/3AC/24VDC/40A

SITOP PSU6200 24 V/40 A stabilized power supply input: 400 - 500 V AC output: 24 V DC/40 A with diagnostic interface



### input

type of the power supply network	3-phase AC or DC
supply voltage at AC	
• minimum rated value	400 V
• maximum rated value	500 V
• initial value	323 V
• full-scale value	576 V
input voltage at DC	450 ... 600 V
buffering time for rated value of the output current in the event of power failure minimum	18 ms
operating condition of the mains buffering	at Vin = 400 V
line frequency	50/60 Hz
line frequency	47 ... 63 Hz
input current	
• at rated input voltage 400 V	1.5 A
• at rated input voltage 500 V	1.2 A
current limitation of inrush current at 25 °C maximum	10 A
fuse protection type in the feeder	three-poled coupled circuit breaker from 4 A characteristic C to 16 A characteristic C or circuit breaker 3RV2011-1EA10 (setting 4 A) or 3RV2711-1ED10 (UL 489)

### output

voltage curve at output	Controlled, isolated DC voltage
number of outputs	1
output voltage at DC rated value	24 V
output voltage	
• at output 1 at DC rated value	24 V
output voltage adjustable	Yes; via potentiometer
adjustable output voltage	24 ... 28 V; max. 960 W (1152 W up to 45°C)
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
• on slow fluctuation of input voltage	0.2 %
• on slow fluctuation of ohm loading	0.1 %
residual ripple	
• maximum	80 mV
• typical	50 mV
voltage peak	
• maximum	80 mV
• typical	30 mV

display version for normal operation	Green LED for 24 V OK
type of signal at output	Electronic contact (NO contact, contact rating 30 V DC/0.1 A) for DC O.K. or diagnostic interface
behavior of the output voltage when switching on	Overshoot of Vout < 2 %
response delay maximum	0.5 s
voltage increase time of the output voltage	
• typical	100 ms
output current	
• rated value	40 A
• rated range	0 ... 40 A; 48 A up to +45°C; +60 ... +70 °C: Derating 3%/K
supplied active power typical	960 W
short-term overload current	
• on short-circuiting during the start-up typical	48 A
• at short-circuit during operation typical	48 A
parallel switching of outputs	can be set with DIP switch
bridging of equipment	Yes; switchable characteristic
number of parallel-switched equipment resources for increasing the power	2
<b>efficiency</b>	
efficiency in percent	96 %
power loss [W]	
• at rated output voltage for rated value of the output current typical	40 W
• during no-load operation maximum	4.5 W
<b>closed-loop control</b>	
relative control precision of the output voltage at load step of resistive load 10/90/10 % typical	2 %
setting time	
• load step 10 to 90% typical	2 ms
• load step 90 to 10% typical	10 ms
• maximum	10 ms
<b>protection and monitoring</b>	
design of the overvoltage protection	< 32 V
property of the output short-circuit proof	Yes
design of short-circuit protection	Shutdown and periodic restart attempts
• typical	48 A
overcurrent overload capability	
• in normal operation	overload capability 150 % Iout rated up to 5 s/min
<b>safety</b>	
galvanic isolation between input and output	Yes
galvanic isolation	ES1 output voltage Vout according to EN 62368-1
operating resource protection class	Class I
leakage current	
• maximum	3.5 mA
protection class IP	IP20
<b>EMC</b>	
standard	
• for emitted interference	EN 55022 Class B
• for mains harmonics limitation	EN 61000-3-2
• for interference immunity	EN 61000-6-2
<b>standards, specifications, approvals</b>	
certificate of suitability	
• CE marking	Yes
• UL approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
• CSA approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
• UKCA marking	Yes
• EAC approval	Yes
• Regulatory Compliance Mark (RCM)	Yes
• NEC Class 2	No
• SEMI F47	Yes

type of certification		Yes; R-41183539
• BIS		Yes
<b>standards, specifications, approvals hazardous environments</b>		
certificate of suitability		No
• IECEx		No
• ATEX		No
• ULhazloc approval		No
• cCSAus, Class 1, Division 2		No
• FM registration		No
<b>standards, specifications, approvals marine classification</b>		
shipbuilding approval		Yes
Marine classification association		
• American Bureau of Shipping Europe Ltd. (ABS)		Yes
• French marine classification society (BV)		No
• Det Norske Veritas (DNV)		Yes
• Lloyds Register of Shipping (LRS)		No
<b>standards, specifications, approvals Environmental Product Declaration</b>		
Environmental Product Declaration		Yes
Global Warming Potential [CO <sub>2</sub> eq]		
• total		1 292.7 kg
• during manufacturing		39.2 kg
• during operation		1 252.1 kg
• after end of life		0.97 kg
Siemens Eco Profile (SEP)		Siemens EcoTech
<b>ambient conditions</b>		
ambient temperature		
• during operation		-30 ... +70; with natural convection a monotonically increasing start-up from -25 °C, safe start-up from -40 °C
• during transport		-40 ... +85
• during storage		-40 ... +85
environmental category according to IEC 60721		Climate class 3K3, 5 ... 95% no condensation
<b>connection method</b>		
type of electrical connection		push-in terminals
• at input		L1, L2, L3, PE: push-in for 0.5 ... 10 mm <sup>2</sup>
• at output		+1, +2, -1, -2, -3: push-in for 0.75 ... 16 mm <sup>2</sup>
• for auxiliary contacts		13, 14 (alarm signal): 1 push-in terminal each for 0.2 ... 1.5 mm <sup>2</sup>
<b>mechanical data</b>		
width × height × depth of the enclosure		95 × 135 × 155 mm
installation width × mounting height		95 mm × 225 mm
required spacing		
• top		45 mm
• bottom		45 mm
• left		0 mm
• right		0 mm
fastening method		Snaps onto DIN rail EN 60715 35x7.5/15
• standard rail mounting		Yes
• S7 rail mounting		No
• wall mounting		No
housing can be lined up		Yes
net weight		2.1 kg
<b>accessories</b>		
electrical accessories		Buffer module, redundancy module
mechanical accessories		Identification labels SIMATIC ET 200SP 6ES7193-6LF30-0AW0
<b>further information internet links</b>		
internet link		
• to website: Industry Mall		<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
• to web page: selection aid TIA Selection Tool		<a href="https://www.siemens.com/tiacloud">https://www.siemens.com/tiacloud</a>
• to website: CAx-Download-Manager		<a href="https://siemens.com/cax">https://siemens.com/cax</a>
• to website: Industry Online Support		<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

additional information	
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
security information	
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a>. (V4.7)</p>

Classifications		Version	Classification
	eClass	14	27-04-07-01
	eClass	12	27-04-07-01
	eClass	9.1	27-04-07-01
	eClass	9	27-04-07-01
	eClass	8	27-04-90-02
	eClass	7.1	27-04-90-02
	eClass	6	27-04-90-02
	ETIM	9	EC002540
	ETIM	8	EC002540
	ETIM	7	EC002540
	IDEA	4	4130
	UNSPSC	15	39-12-10-04

Approvals Certificates	
General Product Approval	



[Manufacturer Declaration](#)



General Product Approval	Marine / Shipping	Environment
--------------------------	-------------------	-------------



[BIS CRS](#)



Siemens  
EcoTech



last modified:

11/19/2024