



Figure similar

SIRIUS safety relay with relay enabling circuits (EC) 24 V AC/DC, 22.5 mm Spring-type terminal EC instantaneous: 4 NO EC delayed: 0 MK for retraction: 1
Expansion unit Maximum achieved SIL / PL: as basic unit

product brand name	SIRIUS
product designation	safety relays
design of the product	extension unit
product type designation	3TK28
Product Function	
product function	
• automatic start	No
• light barrier monitoring	No
• standstill monitoring	No
• protective door monitoring	No
• magnetically operated switch monitoring NC-NO	No
• magnetically operated switch monitoring NC-NC	No
• rotation speed monitoring	No
• laser scanner monitoring	No
• light array monitoring	No
• EMERGENCY OFF function	No
• monitored start-up	No
• pressure-sensitive mat monitoring	No
suitability for interaction press control	No
suitability for use	
• position switch monitoring	No
• EMERGENCY-OFF circuit monitoring	No
• valve monitoring	No
• opto-electronic protection device monitoring	No
• tactile sensor monitoring	No
• magnetically operated switch monitoring	No
• proximity switch monitoring	No
• safety switch	Yes
• safety-related circuits	No
General technical data	
certificate of suitability UL approval	Yes
product feature cross-circuit-proof	No
insulation voltage rated value	300 V
surge voltage resistance rated value	4 000 V
protection class IP	
• of the enclosure	IP40
• of the terminal	IP20
shock resistance	8g / 10 ms
vibration resistance according to IEC 60068-2-6	5 ... 500 Hz: 0,075 mm

operating frequency maximum	1 000 1/h
mechanical service life (operating cycles) typical	10 000 000
electrical endurance (operating cycles) typical	100 000
thermal current of the switching element with contacts maximum	5 A
Substance Prohibitance (Date)	05/01/2012
SVHC substance name	Lead monoxide (lead oxide) - 1317-36-8
Weight	0.233 kg
Ambient conditions	
installation altitude at height above sea level maximum	2 000 m
ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-40 ... +80 °C
relative humidity during operation	10 ... 95 %
air pressure according to SN 31205	90 ... 106 kPa
Electromagnetic compatibility	
installation environment regarding EMC	This product is suitable for Class A environments only. In household environments, this device can cause unwanted radio interference. The user is required to implement appropriate measures in this case.
EMC emitted interference	EN 60947-5-1
Safety related data	
stop category according to IEC 60204-1	0
IEC 62061	
SIL Claim Limit (subsystem) according to EN 62061	3
PFHD with high demand rate according to IEC 62061	1.2E-9 1/h
ISO 13849	
category according to EN ISO 13849-1	4
IEC 61508	
Safety Integrity Level (SIL)	
• according to IEC 61508	3
safety device type according to IEC 61508-2	Type A
Average probability of failure on demand (PFDavg) with low demand rate acc. to IEC 61508	1E-6 1/y
hardware fault tolerance according to IEC 61508	1
T1 value for proof test interval or service life according to IEC 61508	20 a
Electrical Safety	
touch protection against electrical shock	finger-safe
Short-circuit protection	
design of the fuse link for short-circuit protection of the NO contacts of the relay outputs required	gL/gG: 6 A, or quick: 10 A
Inputs	
design of input	
• cascading input/functional switching	No
• feedback input	Yes
• start input	No
Outputs	
number of outputs as contact-affected switching element	
• as NC contact	
— for signaling function instantaneous contact	0
• as NO contact	
— safety-related instantaneous contact	4
— safety-related delayed switching	0
number of outputs as contact-less semiconductor switching element	
• for signaling function	
— delayed switching	0
— instantaneous contact	0
• safety-related	
— delayed switching	0
— instantaneous contact	0
switching capacity current of the NO contacts of the relay outputs at DC-13	

<ul style="list-style-type: none"> • at 24 V • at 115 V • at 230 V 	5 A 0.2 A 0.1 A
switching capacity current of the NO contacts of the relay outputs at AC-15 <ul style="list-style-type: none"> • at 115 V • at 230 V 	5 A 5 A
switching capacity current of the NC contacts of the relay outputs at DC-13 <ul style="list-style-type: none"> • at 24 V • at 115 V • at 230 V 	5 A 0.2 A 0.1 A
switching capacity current of the NC contacts of the relay outputs at AC-15 <ul style="list-style-type: none"> • at 115 V • at 230 V 	5 A 5 A
wire length between sensor and electronics evaluation device with Cu 1.5 mm² and 150 nF/km maximum	1 000 m
Times	
make time with automatic start <ul style="list-style-type: none"> • at DC maximum • at AC maximum 	30 ms 30 ms
make time with automatic start after power failure <ul style="list-style-type: none"> • maximum 	30 ms
backslide delay time in the event of power failure <ul style="list-style-type: none"> • maximum 	25 ms
recovery time after power failure typical	50 ms
Control circuit/ Control	
type of voltage of the control supply voltage	AC/DC
control supply voltage 1 at AC <ul style="list-style-type: none"> • at 50 Hz rated value • at 60 Hz rated value 	24 V 24 V
control supply voltage frequency <ul style="list-style-type: none"> • 1 rated value • 2 rated value 	50 Hz 60 Hz
control supply voltage 1 at DC rated value	24 V
operating range factor control supply voltage rated value of magnet coil at DC <ul style="list-style-type: none"> • initial value • full-scale value 	0.85 1.2
operating range factor control supply voltage rated value of magnet coil at AC <ul style="list-style-type: none"> • at 50 Hz • at 60 Hz 	0.85 ... 1.1 0.85 ... 1.1
Installation/ mounting/ dimensions	
mounting position	any
fastening method	screw and snap-on mounting
height	120 mm
width	22.5 mm
depth	120 mm
Connections/ Terminals	
type of electrical connection	spring-loaded terminals
type of connectable conductor cross-sections <ul style="list-style-type: none"> • solid • finely stranded with core end processing • finely stranded without core end processing • for AWG cables solid • for AWG cables stranded 	2x (0.25 ... 1.5 mm ²) 2 x (0.25 ... 1.5 mm ²) 2x (0.25 ... 1.5 mm ²) 2x (24 ... 16) 2x (24 ... 16)
connectable conductor cross-section <ul style="list-style-type: none"> • solid • finely stranded with core end processing • finely stranded without core end processing 	0.25 ... 1.5 mm ² 0.25 ... 1.5 mm ² 0.25 ... 1.5 mm ²

AWG number as coded connectable conductor cross section	
• solid	24 ... 16
• stranded	24 ... 16
DC resistance of the cable maximum	30 Ω
type of electrical connection plug-in socket	Yes

Approvals Certificates

General Product Approval	EMV	Functional Safety	Test Certificates
--------------------------	-----	-------------------	-------------------



[Type Examination Certificate](#)

[Special Test Certificate](#)

other	Environment
-------	-------------

[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TK2830-2CB30>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TK2830-2CB30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TK2830-2CB30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TK2830-2CB30&lang=en



