

Siemens
EcoTech



LOGO! 12/24RCEO, logic module, power supply / I/O: 12/24 V DC/relay, 8 DI (4 AI)/4 DO, without display, memory 400 blocks, modularly expandable, Ethernet, integrated web server, data log, user-defined web pages, standard microSD card for LOGO! Soft Comfort V8.4 or higher, older projects executable cloud connection, MQTT in all LOGO! 8.4 basic units



Figure similar

Installation type/mounting

Mounting	on 35 mm DIN rail, 4 spacing units wide
----------	---

Supply voltage

Rated value (DC)	Yes
• 12 V DC	Yes
• 24 V DC	Yes
permissible range, lower limit (DC)	10.8 V
permissible range, upper limit (DC)	28.8 V

Time of day

Time switching clocks	
• Number	400; Max. 400, function-specific
• Power reserve	480 h

Digital inputs

Number of digital inputs	8; Of which 4 can be used in analog mode (0 to 10 V)
--------------------------	--

Digital outputs

Number of digital outputs	4; Relays
Short-circuit protection	No; external fusing necessary
Output current	
• for signal "1" permissible range for 0 to 55 °C, max.	10 A

Relay outputs

Switching capacity of contacts	
— with inductive load, max.	3 A
— with resistive load, max.	10 A

EMC

Emission of radio interference acc. to EN 55 011

• Limit class B, for use in residential areas	Yes; Radio interference suppression according to EN55011, Limit Value Class B
---	---

Standards, approvals, certificates

CE mark	Yes
CSA approval	No; covered by UL cert
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes
Marine approval	Yes; in preparation
Ecological footprint	

• environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO ₂ eq]	51.5 kg
— global warming potential, (during production) [CO ₂ eq]	9.64 kg
— global warming potential, (during operation) [CO ₂ eq]	42.1 kg
— global warming potential, (after end of life cycle) [CO ₂ eq]	-0.364 kg
Ambient conditions	
Ambient temperature during operation	
• min.	-20 °C; No condensation
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 080 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Dimensions	
Width	71.5 mm
Height	90 mm
Depth	58 mm

last modified:

10/9/2024 