

Eaton GDA-250MA

Catalog Number: GDA-250MA

Eaton GDA Series Fast-acting fuse, 0.250A, 250 Vac, 32 Vdc (self certified)



General specifications

Product Name	Catalog Number
Eaton Bussmann series GDA fast-acting fuse	GDA-250MA
	UPC
	051712431217
Product Length/Depth	Product Height
20 mm	5 mm
Product Width	Product Weight
5 mm	1 g
Compliances	Certifications
CCC Marked	VDE
CE Marked	Catalog Notes
	High breaking capacity

Product specifications

Type

Electronic

Application

Electronic circuits

Amperage Rating

0.250A

Frequency rating - max

50 Hz

Frequency rating - min

50 Hz

Melting (I²T)

Typical: 0.027 A

Resistance

4.4 ohms DC cold

Voltage drop

1300 mV typical

Interrupt rating

1.5 kAIC at 250 Vac

Fuse indicator

Non-indicating

Connection

Ferrule end x ferrule end

Material

Silver-plated endcap construction

Ceramic tube

Quantity

5

Voltage rating

250 Vac, 32 Vdc (self certified)

Resources

Specifications and datasheets

[Eaton Specification Sheet - GDA-250MA](#)

[Eaton GDA fast-acting fuse data sheet](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)