



Fuse terminal thermoplast Screw terminal on both sides 10 mm Sz. 1.5

Model	
product brand name	ALPHA
type of light source as defect indicator	without
design of the fuse link	others
design of fuse holder	without
General technical data	
insulation material	thermoplastic
terminal contact spacing	10 mm
Supply voltage	
operating voltage rated value	250 V
type of voltage for supply of the defect indicator	others
Protection class	
combustibility class according to UL 94	Other
Main circuit	
operational current rated value	6.3 A
Appearance	
color	miscellaneous
Product details	
product component required end cover plate	No
Number	
number of terminal levels	1
Connections	
connectable conductor cross-section solid	
• minimum	1 mm ²
• maximum	1 mm ²
connectable conductor cross-section stranded	
• maximum	1.5 mm ²
connectable conductor cross-section finely stranded	
• with core end processing minimum	0.75 mm ²
• with core end processing maximum	1.5 mm ²
type of connection 1	screw-type terminal
type of connection 2	screw-type terminal
position of the terminal	lateral
Mechanical Design	
height with lowest-profile installation	42 mm
length	57 mm
fastening method	DIN rail 35 mm
material of the insulating body	Thermoplast
Approvals Certificates	

General Product Approval		other		Environment	
 EG-Konf.	Confirmation		Confirmation	Miscellaneous	Environmental Con- firmations

Environment

[Environmental Con-
firmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1011-1SF12>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WA1011-1SF12>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1SF12

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

12/19/2020 

