

## Twist-Lock® Edge Devices

20A, 250V AC, 2 Pole, 3 Wire Grounding

## Screwless Terminated InsulGrip® Plug

# HUBBELL

### Features

- Faster termination time
- No need for screwdriver and torque wrench
- Spring Termination eliminates strand relaxation
- Funnel shaped wire entry for ease of termination.
- Superior cord grip design protects terminations from excess strain



### Ordering Information

Description	Cord Diameter	UPC	Catalog Number
Black Nylon	360"-.930" (9-24mm)	783585719818	HBL2321STBK

### Listings

Listed to UL 498

Fed.Spec. W-C-596

Certified to CSA C22.2 No.42

### Specifications

Housing / Cord Clamp	Nylon
Terminal Retainer	Nylon
Plunger	Nylon
Blades	Copper Alloy
Terminal Spring Clamp	Spring Steel
Assembly Screws	Zinc Plated Tri-drive
Weight (lbs)	0.25

### Online Resources

[Customer Sales Drawings](#)

[eCatalog](#)

[Installation Instructions](#)

### Performance

#### Electrical

Current Interrupting Certified for current interrupting at full rated current

Dielectric Voltage Withstands 3,000V minimum

#### Mechanical

Terminal Accommodation #14 AWG - #8 AWG stranded copper wire only

Terminal Identification Terminals identified in accordance with UL 498

#### Environmental

Flammability HB or better per UL94/CSA 22.2 No.0.17

Moisture Resistance IP20 Suitability

Operating Temperatures Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

