



## Compression Terminal

By Burndy  
Catalog # [YAL4C2T14](#)

Copper HYLUG™, 2 Hole w/ Inspection Window, 4 AWG, 1/4" Stud, 5/8" Stud Hole Spacing, 8 index, Grey, Short Barrel, Tin Plated.



### Application

Wire Termination

### General

|                                      |                             |
|--------------------------------------|-----------------------------|
| Color Code                           | Gray                        |
| Connector Type                       | STANDARD BARREL             |
| Die Index                            | 8                           |
| Feature - Barrel Style               | Chamfered                   |
| Feature - Barrel Type                | Standard                    |
| Finish Type                          | Tin-Plated                  |
| Material                             | COPPER                      |
| Physical Attribute - Number of Holes | 2                           |
| Physical Attribute - Tongue Type     | Standard                    |
| Plated                               | Y                           |
| Plating Type                         | Tin - Electro Plated        |
| Temperature Rating                   | 194                         |
| Trade Name                           | HYLUG™                      |
| Type                                 | Standard Barrel, Tin Plated |
| UPC                                  | 781810417492                |

### Dimensions

|                                   |          |
|-----------------------------------|----------|
| Dimension - B Length fraction     | 3/4 in   |
| Dimension - B Length inch         | 0.73 in  |
| Dimension - Bolt Hole Size inch   | 0.27 in  |
| Dimension - Bolt Size fraction    | 1/4      |
| Dimension - Bolt Size inch        | 0.25     |
| Dimension - D inch                | 1.20 in  |
| Dimension - Hole Size fraction    | 1/4      |
| Dimension - Hole Size inch        | 0.27     |
| Dimension - Hole Size mm          | 6.9 mm   |
| Dimension - L Length Overall mm   | 56 mm    |
| Dimension - Length Overall inch   | 2.21 in  |
| Dimension - N inch                | 0.25 in  |
| Dimension - Outside Diameter inch | 0.34 in  |
| Dimension - Pad Width inch        | 0.56 in  |
| Dimension - Stud Size fraction    | 1/4      |
| Dimension - Stud Size inch        | 1/4      |
| Dimension - Z (inch)              | 0.32 in  |
| Physical Attribute - Tongue Angle | Straight |

### Electrical Ratings

|                   |       |
|-------------------|-------|
| Voltage - Maximum | 35000 |
| Voltage Rating    | 35 kV |

### Conductor Related

|                                     |        |
|-------------------------------------|--------|
| Conductor - Copper DLO Size Range   | N/A    |
| Conductor - Copper Solid Size       | 4 AWG  |
| Conductor - Copper Solid Size Range | 4 AWG  |
| Conductor - Copper Str Size         | 4 AWG  |
| Conductor - Copper Str Size Range   | 4 AWG  |
| Conductor - Material                | COPPER |
| Conductor Size                      | 4 AWG  |
| Conductor Type                      | CODE   |

### Certifications And Compliance

|                                    |              |
|------------------------------------|--------------|
| Certification - CSA Approved       | Yes          |
| Certification - ETL                | No           |
| Certification - UL Recognized      | No           |
| Certification - cULus              | No           |
| Industry Standard(s)               | UL 486A-486B |
| Standards - RoHS Compliance Status | CM           |
| UL Listed                          | Yes          |

### Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 50 |
|-----------------|----|

### Product Assets

[Catalogs - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Sales Drawings - CSD.029077-01](#)



**A proud member of the Hubbell Family.**