

TradeSelect, Straight Blade Devices,
Residential Grade, Receptacles,
Single, 30A 125/250V, 3-Pole 4-
Wire Grounding, 14-30R, Flush
Mount, Black

By Hubbell Wiring Device-Kellems
Catalog # [RR430F](#)



TradeSELECT® Straight Blade Residential Grade, Single, 30A
125/250V, 3-Pole 4-Wire Grounding, Flush Mount.

Features

- Sequenced contacts assure protection
- Catalog number, ratings and certifications molded in face
- One piece design power and ground contacts

Application

Residential Range and Dryer Devices

General

Catalog Number	RR430F
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Material - Mounting Hardware	Screw Mounting
Number Of Poles	3-Pole
Series	Heavy Duty
Style	Smooth Face
Type	Single Receptacle
UPC	883778100710

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

Electrical Ratings

Amperage Rating	30 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	30 A
Current Rating	30 A

Phase	Single Phase
Voltage Rating	125/250 V
Voltage Rating Description	125/250 V
Wattage	7500

Conductor Related

Number Of Wires	4-Wire
Wire Size	#10 AWG

Certifications And Compliance

Industry Standard(s)	UL Listed
Nema Rating	14-30R

Logistics

Carton Quantity	10
Pallet Quantity	2800

Product Assets

- [Catalog Page - WDK Z-17 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Engineering Drawing - RR430F AutoCAD Drawing](#)
[Installation Manuals - WIRING_PD2193_INSTALLINST](#)
[Literature - Residential Catalog](#)
[Literature - Residential Product Guide](#)
[Sales Drawings - WDK_RR430F_DRAWING_PDF](#)
[Specifications - RR430F Specification Sheet French](#)
[Specifications - WIRING_RR430F_spec](#)
[Warranty - tradeSELECT™ and netSELECT®](#)
[Video - Tradeselect Devices](#)