

Eaton XTOBP24BC1

Catalog Number: XTOBP24BC1

Eaton XT IEC bimetallic overload relay, 0.16-0.24A overload range, 45 mm Frame size, 1NO-1NC contact configuration, Direct mounting, used with 7-15A contactor, 10A trip type



General specifications

Product Name

Eaton XT IEC bimetallic overload relay

Catalog Number

XTOBP24BC1

EAN

4015082784324

Product Length/Depth

3.27 in

Product Height

1.89 in

Product Width

1.77 in

Product Weight

0.3 lb

Compliances

CE Marked
RoHS Compliant
ATEX Compliant

Certifications

UL Listed
CSA Certified
IEC 60947
EN 60947

Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.

Product specifications

Overload range

0.16-0.24 A

Frame size

45 mm

Mounting

Direct

Resources

Brochures

[C440 Electronic Overload Relay](#)

Drawings

[XTOB_BC1 AutoCAD 2D Footprint \(mm\)](#)

[XTOB_BC1 2D Drawing Xchange](#)

[XTOB_BC1 3D Inventor](#)

[XTOB_BC1 AutoCAD 2D Footprint](#)

[XTOB_BC1 3D Model Xchange](#)

[XTOB_BC1 2D PDF](#)

Multimedia

[Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained](#)

Specifications and datasheets

[Global Data Sheet - XTOBP24BC1](#)

[Eaton Specification Sheet - XTOBP24BC1](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
[Eaton.com](#)

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](#)