

## Network Interface Modules



An I/O Network Interface Unit connects VersaPoint I/O modules to a host PLC or computer via a variety of networks, which makes it easy to include VersaPoint I/O in PROFIBUS-DP, Ethernet or DeviceNet installations. Together, the NIU is capable of handling up to 63 modules in one node.

	IC220PNS001	IC220PNS002	IC220EBI001	IC220PBI002	IC220DBI001
<b>Product Name</b>	<b>Profinet Network Interface Unit with 2 Copper Ports</b>	<b>Profinet Network Interface Unit with 2 Fiber Ports</b>	<b>Ethernet TCP/IP Advanced Network Interface Unit - 10/100 Base-T(X) - PCP Support</b>	<b>PROFIBUS-DP Network Interface Unit</b>	<b>DeviceNet Network Interface Unit</b>
<b>Lifecycle Status</b>	Active	Active	Active	Active	Active
<b>Protocol</b>	PROFINET IO	PROFINET IO	Modbus TCP	PROFIBUS DP (V1)	DeviceNet Slave
<b>Data Rate</b>	100 Mbps	100 Mbps	10/100 Base-T(X)	Up to 12Mbps per second	Up to 500 Kbaud
<b>Serial Communications Support</b>	None	None	Yes	Yes	Yes
<b>Firmware Upgrade</b>	No	No	Yes	No	No
<b>Nominal Power Input Voltage</b>	24 VDC	24 VDC	24 VDC	24 VDC	24 VDC
<b>Power Voltage Range</b>	19.2 - 30 VDC	19.2 - 30 VDC	19.2 - 30 VDC	19.2 - 30 VDC	19.2 - 30 VDC
<b>Current for Local Bus UL</b>	0.8 Amp	0.8 Amp	2 Amp	2 Amp	2 Amp
<b>Current for Local Bus UA (ma)</b>	500 mA	500 mA	500 mA	500 mA	500 mA
<b>Maximum Supported Modules</b>	63 (including on-board IO)	63 (including on-board IO)	63	63	63
<b>Digital Inputs</b>	8 @ 24 VDC	8 @ 24 VDC	-	-	-
<b>Digital Outputs</b>	4 @ 24VDC	4 @ 24VDC	-	-	-
<b>Power In</b>	8 Amp maximum	8 Amp maximum	8 Amp maximum	8 Amp maximum	8 Amp maximum
<b>LED Indicators</b>	Bus diagnostics and status indication of voltage	Bus diagnostics and status indication of voltage	Bus diagnostics and status indication of voltage	Bus diagnostics and status indication of voltage	Bus diagnostics and status indication of voltage
<b>Numeric LCD Display</b>	None	None	Yes	None	None
<b>Web Support</b>	None	None	Web Pages SNMP XML Data Monitoring	None	None
<b>Required Terminal Strip</b>	Included	Included	(1) IC220TBK082 (Contains 10 strips)	(1) IC220TBK087 (Contains 10 strips)	(1) IC220TBK201 (Contains 10 strips)
<b>Dimensions (W x H x D)</b>	80 mm x 119.8 mm x 71.5 mm (3.149 in. x 4.717 in. x 2.814 in.)	80 mm x 119.8 mm x 71.5 mm (3.149 in. x 4.717 in. x 2.814 in.)	90 mm x 72 mm x 116 mm (3.543 in. x 2.835 in. x 4.567 in.)	91 mm x 120 mm x 71.5 mm (2.874 in. x 4.724 in. x 2.795 in.)	48.8 mm x 120 mm x 71.5 mm (1.92 in. x 4.72 in. x 2.82 in.)