

CJ Series

Ordering Information

CJ	HPFP	20	V	1N	010	1A	N	L																																																																																						
<table border="1"> <tr> <td rowspan="3">Module connector direction</td> <td>R</td> <td>Right </td> </tr> <tr> <td>L</td> <td>Left </td> </tr> <tr> <td>X</td> <td>Right+Left </td> </tr> <tr> <td rowspan="2">Connection type (terminal block- PLC)</td> <td>N</td> <td>+/- Forward</td> </tr> <tr> <td>P</td> <td>+/- Reverse</td> </tr> <tr> <td rowspan="5">Module type</td> <td>Number+Character</td> <td>Module detailed type signal</td> </tr> <tr> <td>005</td> <td>0.5 m</td> </tr> <tr> <td>010</td> <td>1.0 m</td> </tr> <tr> <td>015</td> <td>1.5 m</td> </tr> <tr> <td>020</td> <td>2.0 m</td> </tr> <tr> <td rowspan="6">Branch</td> <td>P</td> <td>OPEN type</td> </tr> <tr> <td>1N</td> <td>Non-branch</td> </tr> <tr> <td>2S</td> <td>Short 2-branch(for terminal block)</td> </tr> <tr> <td>2L</td> <td>Long 2-branch(for terminal block)</td> </tr> <tr> <td>F2</td> <td>Short up-down 2-branch(for PLC)</td> </tr> <tr> <td>Y2</td> <td>Short right-left 2-branch(for PLC)</td> </tr> <tr> <td rowspan="2">Connector direction of PLC</td> <td>V</td> <td>Vertical</td> </tr> <tr> <td>H</td> <td>Horizontal</td> </tr> <tr> <td rowspan="5">Connector pins of PLC</td> <td>20</td> <td>20-pin</td> </tr> <tr> <td>37</td> <td>37-pin</td> </tr> <tr> <td>40</td> <td>40-pin</td> </tr> <tr> <td>50</td> <td>50-pin</td> </tr> <tr> <td>Connector (terminal block - PLC)</td> <td>HPHP</td> <td>Hirose Plug - Hirose Plug</td> </tr> <tr> <td></td> <td>HPFP</td> <td>Hirose Plug - Fujitsu Plug</td> </tr> <tr> <td></td> <td>HPDP</td> <td>Hirose Plug - D - Sub Plug</td> </tr> <tr> <td></td> <td>HPDS</td> <td>Hirose Plug - D - Sub Socket</td> </tr> <tr> <td></td> <td>HPMP^{※1}</td> <td>Hirose Plug-3M Plug(one-touch)</td> </tr> <tr> <td></td> <td>HPMQ^{※1}</td> <td>Hirose Plug-3M Plug(screw)</td> </tr> <tr> <td></td> <td>HP</td> <td>OPEN - Hirose Plug</td> </tr> <tr> <td></td> <td>FP</td> <td>OPEN - Fujitsu Plug</td> </tr> <tr> <td></td> <td>DP</td> <td>OPEN - D - Sub Plug</td> </tr> <tr> <td></td> <td>DS</td> <td>OPEN - D - Sub Socket</td> </tr> <tr> <td></td> <td>MP^{※1}</td> <td>OPEN - 3M Plug(one-touch)</td> </tr> <tr> <td>Item</td> <td>CJ</td> <td>Junction Cable</td> </tr> </table>									Module connector direction	R	Right 	L	Left 	X	Right+Left 	Connection type (terminal block- PLC)	N	+/- Forward	P	+/- Reverse	Module type	Number+Character	Module detailed type signal	005	0.5 m	010	1.0 m	015	1.5 m	020	2.0 m	Branch	P	OPEN type	1N	Non-branch	2S	Short 2-branch(for terminal block)	2L	Long 2-branch(for terminal block)	F2	Short up-down 2-branch(for PLC)	Y2	Short right-left 2-branch(for PLC)	Connector direction of PLC	V	Vertical	H	Horizontal	Connector pins of PLC	20	20-pin	37	37-pin	40	40-pin	50	50-pin	Connector (terminal block - PLC)	HPHP	Hirose Plug - Hirose Plug		HPFP	Hirose Plug - Fujitsu Plug		HPDP	Hirose Plug - D - Sub Plug		HPDS	Hirose Plug - D - Sub Socket		HPMP ^{※1}	Hirose Plug-3M Plug(one-touch)		HPMQ ^{※1}	Hirose Plug-3M Plug(screw)		HP	OPEN - Hirose Plug		FP	OPEN - Fujitsu Plug		DP	OPEN - D - Sub Plug		DS	OPEN - D - Sub Socket		MP ^{※1}	OPEN - 3M Plug(one-touch)	Item	CJ	Junction Cable
Module connector direction	R	Right 																																																																																												
	L	Left 																																																																																												
	X	Right+Left 																																																																																												
Connection type (terminal block- PLC)	N	+/- Forward																																																																																												
	P	+/- Reverse																																																																																												
Module type	Number+Character	Module detailed type signal																																																																																												
	005	0.5 m																																																																																												
	010	1.0 m																																																																																												
	015	1.5 m																																																																																												
	020	2.0 m																																																																																												
Branch	P	OPEN type																																																																																												
	1N	Non-branch																																																																																												
	2S	Short 2-branch(for terminal block)																																																																																												
	2L	Long 2-branch(for terminal block)																																																																																												
	F2	Short up-down 2-branch(for PLC)																																																																																												
	Y2	Short right-left 2-branch(for PLC)																																																																																												
Connector direction of PLC	V	Vertical																																																																																												
	H	Horizontal																																																																																												
Connector pins of PLC	20	20-pin																																																																																												
	37	37-pin																																																																																												
	40	40-pin																																																																																												
	50	50-pin																																																																																												
	Connector (terminal block - PLC)	HPHP	Hirose Plug - Hirose Plug																																																																																											
	HPFP	Hirose Plug - Fujitsu Plug																																																																																												
	HPDP	Hirose Plug - D - Sub Plug																																																																																												
	HPDS	Hirose Plug - D - Sub Socket																																																																																												
	HPMP ^{※1}	Hirose Plug-3M Plug(one-touch)																																																																																												
	HPMQ ^{※1}	Hirose Plug-3M Plug(screw)																																																																																												
	HP	OPEN - Hirose Plug																																																																																												
	FP	OPEN - Fujitsu Plug																																																																																												
	DP	OPEN - D - Sub Plug																																																																																												
	DS	OPEN - D - Sub Socket																																																																																												
	MP ^{※1}	OPEN - 3M Plug(one-touch)																																																																																												
Item	CJ	Junction Cable																																																																																												

※1 : Cable for SERVO

※If you combine above ordering information randomly, there may be no existing items. It is required to refer to the "■ Cable Selection&Connections, ■ OPEN Type Cable Color, ■ Cable Appearance".

Specifications

Series	CJ SERIES	
Connector for PLC	HIF3BA-20D-2.54R, HIF3BA-40D-2.54R, HIF3BA-50D-2.54R, D-SUB 37P/S, FCN-367J040-AU/F, MDR102 SERIES(20/50pin)	
Connector for terminal block	HIF3BA-20D-2.54R, HIF3BA-40D-2.54R, HIF3BA-50D-2.54R, HIF3BB-50D-2.54R	
Applicable wire	UL 20276 TWIST 20C/40C/50C	
Conductor characteristics	7/0.127mm (AWG 28)×20P, 7/0.127mm (AWG 28)×10P, 7/0.127mm(AWG28)×25P	
Insulation diameter	0.12mm ²	
Cable diameter	Ø7.2mm(40C) / 8.9mm(50C)	
Rated current	Max. 1A	
Conductor resistance	Max. 0.223Ω/m	
Insulation voltage	500VAC 50/60Hz for 1 min.	
Insulation resistance	Min. 15MΩ/km	
Environment	Ambient temperature	-15 to 55°C, storage: -25 to 65°C
	Ambient humidity	35 to 85%RH, storage: 35 to 85%RH

※Environment resistance is rated at no freezing or condensation.

※Applicable cable color is black.

※Conductor resistance value is at 20°C.








● Cable weight

Model	Weight				Model	Weight			
	0.5m	1m	1.5m	2m		0.5m	1m	1.5m	2m
CJ-HPDP37-V1N□□□□□	Approx. 90g	Approx. 127g	Approx. 164g	Approx. 201g	CJ-HPFP40-V1N□□□□□	Approx. 85g	Approx. 122g	Approx. 159g	Approx. 196g
CJ-HPDS37-V1N□□□□□	Approx. 90g	Approx. 127g	Approx. 164g	Approx. 201g	CJ-HPHP40-V1N□□□□□	Approx. 58g	Approx. 95g	Approx. 132g	Approx. 169g
CJ-HPDP37-V2S□□□□□	Approx. 84g	Approx. 121g	Approx. 158g	Approx. 195g	CJ-HPHP20-V1N□□□□□	Approx. 37g	Approx. 66g	Approx. 95g	Approx. 124g
CJ-HPDP37-V2L□□□□□	Approx. 84g	Approx. 121g	Approx. 158g	Approx. 195g	CJ-HPFP40-V2S□□□□□	Approx. 88g	Approx. 125g	Approx. 162g	Approx. 199g
CJ-HPDS37-V2S□□□□□	Approx. 84g	Approx. 121g	Approx. 158g	Approx. 195g	CJ-HPFP40-V2L□□□□□	Approx. 88g	Approx. 125g	Approx. 162g	Approx. 199g
CJ-HPDS37-V2L□□□□□	Approx. 84g	Approx. 121g	Approx. 158g	Approx. 195g	CJ-HPHP40-V2S□□□□□	Approx. 55g	Approx. 92g	Approx. 129g	Approx. 166g
CJ-HPMP20-H1N□□□□□	Approx. 46g	Approx. 74g	Approx. 102g	Approx. 131g	CJ-HPHP40-V2L□□□□□	Approx. 55g	Approx. 92g	Approx. 129g	Approx. 166g
CJ-HPMP50-H1N□□□□□	Approx. 95g	Approx. 150g	Approx. 204g	Approx. 259g	CJ-HPHP40-VY2□□□□□	Approx. 58g	Approx. 95g	Approx. 132g	Approx. 169g
CJ-HPMQ50-H1N□□□□□	Approx. 98g	Approx. 153g	Approx. 207g	Approx. 262g	CJ-HPHP40-VF2□□□□□	Approx. 58g	Approx. 95g	Approx. 132g	Approx. 169g
CJ-FP40-VP□□□	—	Approx. 112g	—	Approx. 186g	CJ-HP20-VP□□□	—	Approx. 62g	—	Approx. 120g
CJ-HP40-VP□□□	—	Approx. 62g	—	Approx. 150g	CJ-MP20-HP□□□	—	Approx. 79g	—	Approx. 137g
CJ-DP37-VP□□□	—	Approx. 117g	—	Approx. 191g	CJ-MP50-HP□□□	—	Approx. 139g	—	Approx. 248g
CJ-DS37-VP□□□	—	Approx. 117g	—	Approx. 191g	CJ-HP50-HP□□□	—	Approx. 131g	—	Approx. 240g

※Cable length 0.5m, 1.5m of OPEN type cable are option.

※Unit weight is except packaging box weight(5g).

■ Connector Direction Of PLC

PLC connector type		Fujitsu plug 40-pin	D-Sub plug 37-pin	D-Sub socket 37-pin	Hirose plug 50-pin	Hirose plug 40-pin	Hirose plug 20-pin	3M socket 50-pin	3M socket 20-pin
PLC module connector direction	R Right 								
	L Left 				—			—	—
	X Right-Left 	—	—	—	—		—	—	—

※Connector direction of terminal block supports only 'R' type.

I/O Terminal Blocks

- AFS(Interface Terminal Block)
- AFL/AFR(Interface Terminal Block)
- ACS(Common Terminal Block)
- AFE(Sensor Connector Terminal Block)
- ABS(Relay Terminal Block)
- ABL(Relay Terminal Block)
- Power Relay

I/O Cables

- MITSUBISHI
- LSIS
- Autonics
- RS Automation
- YOKOGAWA
- FUJII
- KDT
- OMRON
- TELEMECANIQUE
- For SERVO
- Open Type Cables
- Cable Appearance

Remote I/O

- ARD(DeviceNet Digital Standard Terminal Type)
- ARD(DeviceNet Digital Sensor Connector Type)
- ARD(DeviceNet Analog Standard Terminal Type)
- ARM(Modbus Digital Sensor Connector Type)

Others

- Sensor Connectors
- Sockets
- Sensor Distribution Boxes
- Valve Plugs
- Thumbwheel Switches