


G fuse link DIN 41660 quick-response High breaking capacity Rated continuous current 2.5 A



Model			
product brand name		SETRON	
product designation		G fuse link	
design of the product		quick-response (F)	
type of miniature fuse		ceramic fuse	
General technical data			
size of the fuse link		5 x 20 mm	
melting characteristics		quick acting (F)	
type of voltage of the operating voltage		AC	
operating voltage rated value		250 V	
Main circuit			
operational current rated value		2.5 A	
Display and operation			
product component visual defect indication		No	
Mechanical Design			
net weight		1 g	
Approvals Certificates			
General Product Approval		other	Environment



[Confirmation](#)



[Confirmation](#)

[Miscellaneous](#)

[Environmental Con-
firmations](#)

Environment

[Environmental Con-
firmations](#)

Further information
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1822-7EF21
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/8WA1822-7EF21
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1822-7EF21

last modified: 1/14/2024 

