

Data sheet

6GK1503-4CB00

product type designation



PROFIBUS OLM/G22 V4.0

PROFIBUS OLM/G22 V4.0; Optical link module with 2 RS 485 and 2 glass fiber optic cable interfaces (4 BFOC sockets) for standard Distances up to 2850 m; with signaling contact and measuring output.

transfer rate

transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
transfer rate / with PROFIBUS PA	45.45 kbit/s

interfaces

number of electrical/optical connections / for network components or terminal equipment / maximum	4
number of electrical connections	
• for network components or terminal equipment	2
• for measuring device	1
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
type of electrical connection	
• for network components or terminal equipment	9-pin Sub-D socket
• for measuring device	2-pole terminal block
• for power supply and signaling contact	5-pole terminal block
number of optical interfaces / for fiber optic cable	2
design of the optical interface / for fiber optic cable	BFOC port

optical data

attenuation factor / of the FOC transmission link	
• for glass FOC with 50/125 µm / at 3 dB/km / maximum	10 dB
• for glass FOC with 62.5/125 µm / at 3.5 dB/km / maximum	12 dB
propagation delay [bit]	6.5 bit
connectable optical power relative to 1 mW	
• for glass FOC with 50/125 µm / at 3 dB/km	-16 dB
• for glass FOC with 62.5/125 µm / at 3.5 dB/km	-13 dB
optical sensitivity relating to 1 mW	
• for glass FOC with 50/125 µm / at 3 dB/km	-28 dB
• for glass FOC with 62.5/125 µm / at 3.5 dB/km	-28 dB
wavelength / of the optical interface / note	860 nm, multimode
wire length	
• for glass FOC with 50/125 µm / at 3 dB/km / maximum	3 km
• for glass FOC with 62.5/125 µm / at 3.5 dB/km / maximum	3 km

signal inputs/outputs

operating voltage / of the signaling contacts / at DC / rated value	24 V
operational current / of the signaling contacts / at DC / maximum	0.1 A

supply voltage, current consumption, power loss

type of voltage / of the supply voltage	DC
---	----

supply voltage / at DC / rated value	24 V
supply voltage / at DC	18.8 ... 28.8 V
product component / fusing at power supply input	Yes
consumed current / at DC / at 24 V / maximum	0.2 A
ambient conditions	
ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP40
design, dimensions and weights	
design	compact
width	39.5 mm
height	112 mm
depth	74.5 mm
net weight	340 g
fastening method	
• 35 mm DIN-rail mounting	Yes
• wall mounting	Yes
product functions / redundancy	
product function / ring redundancy	Yes
standards, specifications, approvals	
standard	
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 Nr. 60950-1
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
certificate of suitability	
• CE marking	EN 61000-6-2, EN 61000-6-4
• C-Tick	Yes
• C-Tick	Yes
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• French marine classification society (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Germanische Lloyd (GL)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
reference code	
• according to IEC 81346-2:2019	KGC
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
standards, specifications, approvals / hazardous environments	
certificate of suitability / CCC / for hazardous zone according to GB standard	No
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
• total	165.41 kg
• during manufacturing	15.09 kg
• during operation	150.26 kg
• after end of life	0.06 kg
further information / internet links	
internet link	
• to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
• to website: Industrial communication	https://siemens.com/industrial-communication
• to web page: SiePortal	https://sieportal.siemens.com/
• to website: Image database	https://www.automation.siemens.com/bilddb
• to website: CAx-Download-Manager	https://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval



[Declaration of Conformity](#)



General Product Approval

EMV

For use in hazardous locations

Marine / Shipping

Miscellaneous



KC



KEMA



DNV



LRS

Marine / Shipping

Environment



[Confirmation](#)



last modified:

2/18/2025