



Figure similar

*** Spare part *** SIMATIC DP, Electronics module for ET 200S, 2 AI Standard U 15 mm width, +/-10V; 13 bit+sign +/-5 V; 12 bit+sign, 1..5 V; 12-bit Cycle time 65 ms/channel with SF LED (group fault)

General information	
Product function	
• Isochronous mode	No
Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V; From power module
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	30 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
• Address space per module, max.	4 byte
Analog inputs	
Number of analog inputs	2
permissible input voltage for voltage input (destruction limit), max.	35 V; 35 V continuous; 75 V for max. 1 ms (mark to space ratio 1:20)
Cycle time (all channels) max.	Number of active channels per module x basic conversion time
Input ranges (rated values), voltages	
• 1 V to 5 V	Yes
• -10 V to +10 V	Yes
• -5 V to +5 V	Yes
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	14 bit; ±10 V: 13 bit + sign, ±5 V: 13 bit + sign; 1 to 5 V: 13 bit
• Integration time, parameterizable	Yes
• Integration time (ms)	16,7 / 20 ms
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
• Conversion time (per channel)	65 ms; 55 / 65 ms
Smoothing of measured values	
• parameterizable	Yes; In four stages by means of digital filtering
• Step: None	Yes; 1x cycle time
• Step: low	Yes; 4x cycle time

• Step: Medium • Step: High		Yes; 32x cycle time																																							
		Yes; 64x cycle time																																							
Errors/accuracies																																									
Operational error limit in overall temperature range																																									
• Voltage, relative to input range, (+/-)	0.6 %																																								
Basic error limit (operational limit at 25 °C)																																									
• Voltage, relative to input range, (+/-)	0.4 %																																								
Interrupts/diagnostics/status information																																									
Diagnoses																																									
• Wire-break • Group error • Overflow/underflow	Yes; Measuring range 1 to 5 V only Yes Yes																																								
Diagnostics indication LED																																									
• Group error SF (red)	Yes																																								
Parameter																																									
Remark	4 byte																																								
Diagnostics wire break	Disable / enable (only in measuring range 1 to 5 V)																																								
Group diagnostics	Disable / enable																																								
Overflow/underflow	Disable / enable																																								
Potential separation																																									
Potential separation analog inputs																																									
• between the channels • between the channels and backplane bus • Between the channels and load voltage L+	No Yes Yes																																								
Isolation																																									
Isolation tested with	500 V DC																																								
Dimensions																																									
Width	15 mm																																								
Height	81 mm																																								
Depth	52 mm																																								
Weights																																									
Weight, approx.	40 g																																								
Classifications																																									
		<table><tr><th></th><th>Version</th><th>Classification</th></tr><tr><td>eClass</td><td>14</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>12</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>9.1</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>9</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>8</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>6</td><td>27-24-26-01</td></tr><tr><td>ETIM</td><td>9</td><td>EC001596</td></tr><tr><td>ETIM</td><td>8</td><td>EC001596</td></tr><tr><td>ETIM</td><td>7</td><td>EC001596</td></tr><tr><td>IDEA</td><td>4</td><td>3562</td></tr><tr><td>UNSPSC</td><td>15</td><td>32-15-17-05</td></tr></table>		Version	Classification	eClass	14	27-24-26-01	eClass	12	27-24-26-01	eClass	9.1	27-24-26-01	eClass	9	27-24-26-01	eClass	8	27-24-26-01	eClass	7.1	27-24-26-01	eClass	6	27-24-26-01	ETIM	9	EC001596	ETIM	8	EC001596	ETIM	7	EC001596	IDEA	4	3562	UNSPSC	15	32-15-17-05
	Version	Classification																																							
eClass	14	27-24-26-01																																							
eClass	12	27-24-26-01																																							
eClass	9.1	27-24-26-01																																							
eClass	9	27-24-26-01																																							
eClass	8	27-24-26-01																																							
eClass	7.1	27-24-26-01																																							
eClass	6	27-24-26-01																																							
ETIM	9	EC001596																																							
ETIM	8	EC001596																																							
ETIM	7	EC001596																																							
IDEA	4	3562																																							
UNSPSC	15	32-15-17-05																																							
Approvals / Certificates																																									
General Product Approval																																									
Manufacturer Declaration	 EG-Konf.	  UL																																							
		 RCM																																							
EMV	For use in hazardous locations																																								



[FM](#)



For use in hazardous locations

Marine / Shipping



[Miscellaneous](#)

[CCC-Ex](#)



Marine / Shipping



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

last modified:

5/22/2024