SIEMENS

Data sheet 3RA6860-6AB

PE infeed Connection main circuit: screw terminal Connection terminal maximum 25 mm2 / 35 mm2

General technical data		
product brand name		SIRIUS
product designation		PE infeed
protection class IP on the front according to IEC 60529		IP00
degree of pollution		3
installation altitude at height above sea level maximum	m	2 000
ambient temperature		
● during transport	°C	-55 ... +80
● during storage	°C	-55 ... +80
● during operation	°C	-20 ... +60
vibration resistance		f = 4 to 5.8 Hz; d = 15 mm; f = 5.8 to 500 Hz; a = 2 m / s2 10 cycles
shock resistance		Semi-sinusoidal a = 6 m/s2 at 10 ms; 3 pos. and 3 neg. Shock in all axes
reference code		
● according to IEC 81346-2		W
● according to EN 61346-2		W
Main circuit		
operational current at AC at 400 V rated value	A	63
Installation/ mounting/ dimensions		
fastening method		plug-in fixing
width	mm	32
height	mm	65
depth	mm	70
Connections/ Terminals		
type of electrical connection for main current circuit		screw-type terminals
design of screw-type connection for main contacts		M3
stripped length for main contacts	mm	13
tightening torque for main contacts with screw-type terminals	N·m	3 ... 4.5
type of connectable conductor cross-sections for supply for main contacts using the upper clamping point		
● solid		2.5 ... 35 mm²
● stranded		2.5 ... 35 mm²
● finely stranded with core end processing		2.5 ... 25 mm²
● finely stranded without core end processing		2.5 ... 25 mm²
type of connectable conductor cross-sections for supply for main contacts using the lower clamping point		
● solid		2.5 ... 35 mm²
● stranded		2.5 ... 35 mm²
● finely stranded with core end processing		2.5 ... 25 mm²
● finely stranded without core end processing		2.5 ... 25 mm²

Subject to change without notice
© Copyright Siemens

type of connectable conductor cross-sections for supply for main contacts using both clamping points		
● solid		2 x (2.5 ... 25 mm²)
● stranded		2 x (2.5 ... 25 mm²)
● finely stranded with core end processing		2 x (2.5 ... 16 mm²)
● finely stranded without core end processing		2 x (2.5 ... 16 mm²)
type of connectable conductor cross-sections for AWG cables		
● for supply for main contacts using the upper clamping point		12 ... 2
● for supply for main contacts using the lower clamping point		12 ... 2
● for supply for main contacts using both clamping points		2 x (16 ... 2)

Certificates/ approvals

General Product Approval	EMV	Test Certificates
		Type Test Certificates/Test Report

Marine / Shipping	other	Environment
	Confirmation	Environmental Confirmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA6860-6AB
Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA6860-6AB
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RA6860-6AB
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA6860-6AB&lang=en

Subject to change without notice
© Copyright Siemens



last modified: 4/2/2025

Subject to change without notice
© Copyright Siemens