



circuit breaker VL150X UL, type CG (cat no. NCX3B030) non-interchangeable frame, with circuit breaker approval acc. to UL 489 standard breaking capacity 3-pole, NEMA rating 35kA/480V (molded case circuit breaker) Electronic Trip Unit TM, LI function TA=40°C In=<30A rated current II=300A short-circuit protection IR=30A Electronic Trip Unit for line protection without connection accessories without auxiliary release without auxiliary/alarm switch

Weight	2 kg
Net Weight	2 kg

General Product Approval	Test Certificates	other	Environment
--------------------------	-------------------	-------	-------------



[Special Test Certificate](#)

[Confirmation](#)

[Miscellaneous](#)

[Environmental Confirmations](#)

[Environmental Confirmations](#)

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL1103-1KM30-0AA0>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3VL1103-1KM30-0AA0>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL1103-1KM30-0AA0
- CAX-Online-Generator
<http://www.siemens.com/cax>
- Information- and Downloadcenter (catalogues, leaflets,...)
<http://www.siemens.com/energy-automation>



last modified: 6/30/2024

