P-FU 5X20 LED 24 - Fuse plug



https://www.phoenixcontact.com/in/products/3036819



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Fuse plug, Prior to replacing the cartridge fuse, disconnect the fuse connector from the basic terminal block., nom. voltage: 24 V, nominal current: 6.3 A, fuse type: G / 5 x 20, mounting type: Plug-in mounting, color: black

Your advantages

- · Large-surface labeling option
- · Test contacts on both sides of the fuse
- · Versions with bipolar error display
- · Can be used for overload/short-circuit protection

Commercial data

| Item number | 3036819 |
|--------------------------------------|---------------|
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | BE2 |
| Product key | BE2Z3X |
| GTIN | 4017918943905 |
| Weight per piece (including packing) | 4.21 g |
| Weight per piece (excluding packing) | 4.07 g |
| Customs tariff number | 85369095 |
| Country of origin | PL |

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in