

# MCR-SL-CUC-200-I - Universal current transducer



2308030

<https://www.phoenixcontact.com/in/products/2308030>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Universal current transducer, for measuring AC, DC, and distorted currents, 0 ... 200 A input current, 4 ... 20 mA output

## Your advantages

- Variable mounting on DIN rail and mounting panel
- Compact dimensions also enable distributed use
- Simple connection technology thanks to COMBICON plug-in connection terminal blocks
- 3-way isolation
- Universal current measurement, no shunt required

## Commercial data

Item number	2308030
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CK4
Product key	CMMA31
GTIN	4046356434058
Weight per piece (including packing)	297.3 g
Weight per piece (excluding packing)	293.6 g
Customs tariff number	90303370
Country of origin	CN

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.  
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420  
[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)