



Figure similar

SIMATIC S7-1500F, CPU 1517F-3 PN/DP, central processing unit with work memory 3 MB for program and 8 MB for data, 1st interface: PROFINET IRT with 2-port switch, 2nd interface: PROFINET RT, 3rd interface: PROFIBUS, 2 ns bit performance, SIMATIC Memory Card required

General information	
Product type designation	CPU 1517F-3 PN/DP
HW functional status	FS11
Firmware version	V3.1
• FW update possible	Yes
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	Yes; Distributed and central; with minimum OB 6x cycle of 250 µs (distributed) and 1 ms (central)
• SysLog	Yes
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V19 (FW V3.1); V13 Update 3 (FW V1.6) or higher
Configuration control	
via dataset	Yes
Display	
Screen diagonal [cm]	6.1 cm
Control elements	
Number of keys	6
Mode selector switch	1
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
• Repeat rate, min.	1/s
Input current	
Current consumption (rated value)	1.55 A
Current consumption, max.	1.9 A
Inrush current, max.	1.9 A; Rated value
I ² t	0.4 A ² s
Power	
Infeed power to the backplane bus	12 W
Power consumption from the backplane bus (balanced)	30 W
Power loss	
Power loss, typ.	24 W
Memory	
Number of slots for SIMATIC memory card	1

SIMATIC memory card required		Yes		
Work memory				
• integrated (for program)	3 Mbyte			
• integrated (for data)	8 Mbyte			
Load memory				
• Plug-in (SIMATIC Memory Card), max.	32 Gbyte			
Backup				
• maintenance-free	Yes			
CPU processing times				
for bit operations, typ.	2 ns			
for word operations, typ.	3 ns			
for fixed point arithmetic, typ.	3 ns			
for floating point arithmetic, typ.	12 ns			
CPU-blocks				
Number of elements (total)	12 000; Blocks (OB, FB, FC, DB) and UDTs			
DB				
• Number range	1 ... 60 999; subdivided into: number range that can be used by the user: 1 ... 59 999, and number range of DBs created via SFC 86: 60 000 ... 60 999			
• Size, max.	8 Mbyte; For DBs with absolute addressing, the max. size is 64 KB			
FB				
• Number range	0 ... 65 535			
• Size, max.	1 Mbyte			
FC				
• Number range	0 ... 65 535			
• Size, max.	1 Mbyte			
OB				
• Size, max.	1 Mbyte			
• Number of free cycle OBs	100			
• Number of time alarm OBs	20			
• Number of delay alarm OBs	20			
• Number of cyclic interrupt OBs	20; with minimum OB 3x cycle of 100 µs			
• Number of process alarm OBs	50			
• Number of DPV1 alarm OBs	3			
• Number of isochronous mode OBs	3			
• Number of technology synchronous alarm OBs	2			
• Number of startup OBs	100			
• Number of asynchronous error OBs	4			
• Number of synchronous error OBs	2			
• Number of diagnostic alarm OBs	1			
Nesting depth				
• per priority class	24; Up to 8 possible for F-blocks			
Counters, timers and their retentivity				
S7 counter				
• Number	2 048			
Retentivity				
— adjustable	Yes			
IEC counter				
• Number	Any (only limited by the main memory)			
Retentivity				
— adjustable	Yes			
S7 times				
• Number	2 048			
Retentivity				
— adjustable	Yes			
IEC timer				
• Number	Any (only limited by the main memory)			
Retentivity				
— adjustable	Yes			
Data areas and their retentivity				
Retentive data area (incl. timers, counters, flags), max.	768 kbyte; In total; available retentive memory for bit memories, timers, counters, DBs, and technology data (axes): 700 KB			

Extended retentive data area (incl. timers, counters, flags), max.	8 Mbyte; When using PS 6 0W 24/48/60 V DC HF
Flag	
• Size, max.	16 kbyte
• Number of clock memories	8; 8 clock memory bit, grouped into one clock memory byte
Data blocks	
• Retentivity adjustable	Yes
• Retentivity preset	No
Local data	
• per priority class, max.	64 kbyte; max. 16 KB per block
Address area	
Number of IO modules	16 384; max. number of modules / submodules
I/O address area	
• Inputs	32 kbyte; All inputs are in the process image
• Outputs	32 kbyte; All outputs are in the process image
per integrated IO subsystem	
— Inputs (volume)	32 kbyte; Max. 32 KB via X1; max. 8 KB via X2 or X3
— Outputs (volume)	32 kbyte; Max. 32 KB via X1; max. 8 KB via X2 or X3
per CM/CP	
— Inputs (volume)	8 kbyte
— Outputs (volume)	8 kbyte
Subprocess images	
• Number of subprocess images, max.	32
Hardware configuration	
Number of distributed I/O systems	64; A distributed I/O system is characterized not only by the integration of distributed I/O via PROFINET or PROFIBUS communication modules, but also by the connection of I/O via AS-i master modules or links (e.g. IE/PB-Link)
Number of DP masters	
• integrated	1
• Via CM	8; A maximum of 8 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total
Number of IO Controllers	
• integrated	2
• Via CM	8; A maximum of 8 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total
Rack	
• Modules per rack, max.	32; CPU + 31 modules
• Number of lines, max.	1
PtP CM	
• Number of PtP CMs	the number of connectable PtP CMs is only limited by the number of available slots
Time of day	
Clock	
• Type	Hardware clock
• Backup time	6 wk; At 40 °C ambient temperature, typically
• Deviation per day, max.	10 s; Typ.: 2 s
Operating hours counter	
• Number	16
Clock synchronization	
• supported	Yes
• to DP, master	Yes
• on DP, device	Yes
• in AS, master	Yes
• in AS, device	Yes
• on Ethernet via NTP	Yes
Interfaces	
Number of PROFINET interfaces	2
Number of PROFIBUS interfaces	1
1. Interface	
Interface types	
• RJ 45 (Ethernet)	Yes; X1
• Number of ports	2
• integrated switch	Yes