



- FINGER GUARDS OPTIONAL
- OPTIONAL FUSE BLOCK WILL ADD 1.3"[33mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WITH FINGER GUARD WILL ADD 1.5"[38mm] TO HEIGHT
- TOLERANCES STD. +/- 0.1" [+/-3mm]
- ALL DIMENSIONS ARE IN INCHES [mm]

H1 OV 240 230 220 ↓ HV TERMINAL LOCATION MADE IN MEXICO SN	H2 480 460 440 ↓ LV TERMINAL LOCATION	H3 600 575 550 ↓ LV TERMINAL LOCATION	H4 600 575 550 ↓ LV TERMINAL LOCATION			CONTROL TRANSFORMER P/N C2G0075MBMH 75 VA 252L E50394 PDG12 TYPE 3AH LISTED LR3902 TYPE 3AH	P/N C2G0075MBMH 75 VA 50/60 Hz 130°C CLASS LISTED 252L E50394 PDG12 TYPE 3AH LR3902 TYPE 3AH	LV TERMINAL LOCATION 120 100 115 96 110 92 X3 X2 X1 GND
------------------------------------------------------------------------------------	------------------------------------------------------	------------------------------------------------------	------------------------------------------------------	--	--	------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------

NOTES:



TITLE: 1 PHASE GENERAL PURPOSE CONTROL TFX

1	25/09/16	RH	UPDATED EDB	DES: MSARAF
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 1 OF 1

EDBC2G0075MBMH