



- FINGER GUARDS FOR TERMINAL BLOCKS AND FUSING OPTIONAL
- OPTIONAL FUSE CLIPS WILL ADD 0.31"[9mm] TO HEIGHT
- OPTIONAL FUSE CLIPS WITH FINGER GUARDS WILL ADD 0.44"[11mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WILL ADD 1.3"[33mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WITH FINGER GUARD WILL ADD 1.5"[38mm] TO HEIGHT
- TOLERANCES STD. +/- 0.1"[+/-3mm]
- ALL DIMENSIONS ARE IN INCHES [mm]

<table border="0"> <tr> <td>H1</td><td>H2</td><td>H3</td><td>H4</td></tr> <tr> <td>OV</td><td>240</td><td>480</td><td>600</td></tr> <tr> <td></td><td>230</td><td>460</td><td>575</td></tr> <tr> <td></td><td>220</td><td>440</td><td>550</td></tr> </table> <p>HV TERMINAL LOCATION</p> <p><b>hps</b></p> <p>MADE IN MEXICO SN</p>	H1	H2	H3	H4	OV	240	480	600		230	460	575		220	440	550		<p>UL LISTED 252L E50394 PDG12 TYPE 3AH</p> <p><b>hammond</b> POWER SOLUTIONS</p> <p>CONTROL TRANSFORMER P/N C2G0750MBMH 750 VA</p> <p>LR3902 TYPE 3AH</p>	<p>UL LISTED 252L E50394 PDG12 TYPE 3AH</p> <p>P/N C2G0750MBMH 750 VA 60/60 Hz 130°C CLASS</p> <table border="0"> <tr> <td>LV TERMINAL LOCATION</td> <td></td> <td></td> </tr> <tr> <td>120</td><td>100</td><td>OV</td></tr> <tr> <td>115</td><td>95</td><td></td></tr> <tr> <td>110</td><td>90</td><td></td></tr> <tr> <td>X3</td><td>X2</td><td>X1</td></tr> <tr> <td></td><td></td><td>GND</td></tr> </table>	LV TERMINAL LOCATION			120	100	OV	115	95		110	90		X3	X2	X1			GND
H1	H2	H3	H4																																		
OV	240	480	600																																		
	230	460	575																																		
	220	440	550																																		
LV TERMINAL LOCATION																																					
120	100	OV																																			
115	95																																				
110	90																																				
X3	X2	X1																																			
		GND																																			

NOTES:



TITLE: 1 PHASE GENERAL PURPOSE CONTROL TFX

1	25/09/16	RH	UPDATED EDB	DES: MSARAF
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 1 OF 1

EDBC2G0750MBMH