



- FINGER GUARDS FOR TERMINAL BLOCKS AND FUSING OPTIONAL
- OPTIONAL FUSE CLIPS WILL ADD 0.35"[9mm] TO HEIGHT
- OPTIONAL FUSE CLIPS WITH FINGER GUARDS WILL ADD 0.48"[12mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WILL ADD 1.3"[33mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WITH FINGER GUARD WILL ADD 1.5"[38mm] TO HEIGHT
- TOLERANCES STD. +/- 0.1"[+/-3mm]
- ALL DIMENSIONS ARE IN INCHES [mm]

<table border="0"> <tr><td>H1</td><td>H3</td><td>H2</td><td>H4</td></tr> <tr><td>220</td><td>440</td><td>440</td><td>440</td></tr> <tr><td>230</td><td>460</td><td>460</td><td>460</td></tr> <tr><td>240</td><td>480</td><td>480</td><td>480</td></tr> </table>	H1	H3	H2	H4	220	440	440	440	230	460	460	460	240	480	480	480				<table border="0"> <tr><td>H1</td><td>H3</td><td>H2</td><td>H4</td></tr> <tr><td colspan="4">CONTROL TRANSFORMER</td></tr> <tr><td colspan="4">P/N C2G0500MQM</td></tr> <tr><td colspan="4">500 VA</td></tr> <tr><td colspan="4">T2 T1 X2 X1 GND</td></tr> </table>	H1	H3	H2	H4	CONTROL TRANSFORMER				P/N C2G0500MQM				500 VA				T2 T1 X2 X1 GND					<table border="0"> <tr><td>P/N</td><td>C2G0500MQM</td></tr> <tr><td>500 VA</td><td>50/60 Hz</td></tr> <tr><td>130°C CLASS</td><td></td></tr> </table>	P/N	C2G0500MQM	500 VA	50/60 Hz	130°C CLASS		<table border="0"> <tr><td>LV TERMINAL LOCATION</td><td></td></tr> <tr><td>120</td><td>0V</td></tr> <tr><td>115</td><td></td></tr> <tr><td>110</td><td></td></tr> <tr><td>X2</td><td>X1</td></tr> <tr><td></td><td>GND</td></tr> </table>	LV TERMINAL LOCATION		120	0V	115		110		X2	X1		GND
H1	H3	H2	H4																																																										
220	440	440	440																																																										
230	460	460	460																																																										
240	480	480	480																																																										
H1	H3	H2	H4																																																										
CONTROL TRANSFORMER																																																													
P/N C2G0500MQM																																																													
500 VA																																																													
T2 T1 X2 X1 GND																																																													
P/N	C2G0500MQM																																																												
500 VA	50/60 Hz																																																												
130°C CLASS																																																													
LV TERMINAL LOCATION																																																													
120	0V																																																												
115																																																													
110																																																													
X2	X1																																																												
	GND																																																												

NOTES:



TITLE: 1 PHASE GENERAL PURPOSE CONTROL TFX

1	25/09/16	RH	UPDATED EDB	DES: MSARAF
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 1 OF 1

EDBC2G0500MQM