



- FINGER GUARDS FOR TERMINAL BLOCKS AND FUSING OPTIONAL
- OPTIONAL FUSE CLIPS WILL ADD 0.15 [4mm] TO HEIGHT
- OPTIONAL FUSE CLIPS WITH FINGER GUARDS WILL ADD 0.28 [7mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WILL ADD 1.3 [33mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WITH FINGER GUARD WILL ADD 1.5 [38mm] TO HEIGHT
- TOLERANCES STD. +/- 0.1 [ +/- 3mm]
- ALL DIMENSIONS ARE IN INCHES [mm]

	<table border="1"> <tr><th>H1</th><th>H3</th><th>H2</th><th>H4</th></tr> <tr><td>220</td><td>440</td><td>440</td><td>440</td></tr> <tr><td>230</td><td>460</td><td>460</td><td>460</td></tr> <tr><td>240</td><td>480</td><td>480</td><td>480</td></tr> </table>	H1	H3	H2	H4	220	440	440	440	230	460	460	460	240	480	480	480	 252L E50394 180-7 TYPE 3AH	 <b>hammond</b> POWER SOLUTIONS	  LR3902 TYPE 3AH	 252L E50394 180-7 TYPE 3AH		P/N C2G2000QM/J 2000 VA 50/60 Hz 180°C CLASS				
	H1	H3	H2	H4																							
220	440	440	440																								
230	460	460	460																								
240	480	480	480																								
HV TERMINAL LOCATION <table border="1"> <tr><th>1</th><th>2</th><th>4</th></tr> <tr><td>3</td><td>2</td><td>4</td></tr> </table>	1	2	4	3	2	4	LV TERMINAL LOCATION <table border="1"> <tr><th>1</th><th>2</th><th>3</th><th>4</th></tr> <tr><td>120</td><td>240</td><td>230</td><td>220</td></tr> <tr><td>110</td><td>230</td><td>220</td><td>220</td></tr> <tr><td>X4</td><td>X2</td><td>X3</td><td>X1</td></tr> <tr><td></td><td></td><td></td><td>GND</td></tr> </table>	1	2	3	4	120	240	230	220	110	230	220	220	X4	X2	X3	X1				GND
1	2	4																									
3	2	4																									
1	2	3	4																								
120	240	230	220																								
110	230	220	220																								
X4	X2	X3	X1																								
			GND																								

NOTES:



TITLE: 1 PHASE GENERAL PURPOSE CONTROL TFX

1	25/09/16	RH	UPDATED EDB	DES: TARMENIA
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 1 OF 1

EDBC2G2000QM/J