



- FINGER GUARDS OPTIONAL
- OPTIONAL FUSE BLOCK WILL ADD 1.3"[33mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WITH FINGER GUARD WILL ADD 1.5"[38mm] TO HEIGHT
- TOLERANCES STD. +/- 0.1"[+/-3mm]
- ALL DIMENSIONS ARE IN INCHES [mm]

<table border="0"> <tr><td>H1</td><td>H3</td><td>H2</td><td>H4</td></tr> <tr><td>220</td><td>440</td><td>440</td><td>440</td></tr> <tr><td>230</td><td>460</td><td>460</td><td>460</td></tr> <tr><td>240</td><td>480</td><td>480</td><td>480</td></tr> </table>	H1	H3	H2	H4	220	440	440	440	230	460	460	460	240	480	480	480			<table border="0"> <tr><td>H1</td><td>H3</td><td>H2</td><td>H4</td></tr> <tr><td>252L</td><td>E50394</td><td>PDG12</td><td>TYPE 3AH</td></tr> </table>	H1	H3	H2	H4	252L	E50394	PDG12	TYPE 3AH	<table border="0"> <tr><td>LISTED</td><td>252L</td><td>E50394</td><td>PDG12</td><td>TYPE 3AH</td></tr> <tr><td>LR3902</td><td>TYPE 3AH</td><td>CE</td><td>CE</td><td>CE</td></tr> </table>	LISTED	252L	E50394	PDG12	TYPE 3AH	LR3902	TYPE 3AH	CE	CE	CE	<table border="0"> <tr><td>P/N</td><td>C2G0150QR</td><td>150 VA</td><td>50/60 Hz</td><td>130°C CLASS</td></tr> <tr><td>LISTED</td><td>252L</td><td>E50394</td><td>PDG12</td><td>TYPE 3AH</td></tr> <tr><td>LR3902</td><td>TYPE 3AH</td><td>CE</td><td>CE</td><td>CE</td></tr> </table>	P/N	C2G0150QR	150 VA	50/60 Hz	130°C CLASS	LISTED	252L	E50394	PDG12	TYPE 3AH	LR3902	TYPE 3AH	CE	CE	CE	<table border="0"> <tr><td>LV TERMINAL LOCATION</td><td>24</td><td>23</td><td>22</td><td>X2</td><td>X1</td><td>GND</td></tr> <tr><td></td><td>0V</td><td></td><td></td><td></td><td></td><td></td></tr> </table>	LV TERMINAL LOCATION	24	23	22	X2	X1	GND		0V					
H1	H3	H2	H4																																																																		
220	440	440	440																																																																		
230	460	460	460																																																																		
240	480	480	480																																																																		
H1	H3	H2	H4																																																																		
252L	E50394	PDG12	TYPE 3AH																																																																		
LISTED	252L	E50394	PDG12	TYPE 3AH																																																																	
LR3902	TYPE 3AH	CE	CE	CE																																																																	
P/N	C2G0150QR	150 VA	50/60 Hz	130°C CLASS																																																																	
LISTED	252L	E50394	PDG12	TYPE 3AH																																																																	
LR3902	TYPE 3AH	CE	CE	CE																																																																	
LV TERMINAL LOCATION	24	23	22	X2	X1	GND																																																															
	0V																																																																				

HV TERMINAL LOCATION: 1 3 2 4 | 1 3 2 4
MADE IN MEXICO
SN

NOTES:



TITLE: 1 PHASE GENERAL PURPOSE CONTROL TFX

1	25/09/16	RH	UPDATED EDB	DES: MSARAF
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 1 OF 1

EDBC2G0150QR

1.1_jwen 2025/09/22 10:27

THIS DRAWING CONTAINS STRICTLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES.