



- FINGER GUARDS FOR TERMINAL BLOCKS AND FUSING OPTIONAL
- OPTIONAL FUSE CLIPS WILL ADD 0.35"[9mm] TO HEIGHT
- OPTIONAL FUSE CLIPS WITH FINGER GUARDS WILL ADD 0.48"[12mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WILL ADD 1.3"[33mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WITH FINGER GUARD WILL ADD 1.5"[38mm] TO HEIGHT
- TOLERANCES STD. +/- 0.1"[+/-3mm]
- ALL DIMENSIONS ARE IN INCHES [mm]

<table border="0"> <tr><td>H1</td><td>H3</td><td>H2</td><td>H4</td></tr> <tr><td>190</td><td>380</td><td>398</td><td>240</td></tr> <tr><td>199</td><td></td><td>416</td><td></td></tr> <tr><td>208</td><td></td><td></td><td></td></tr> </table>	H1	H3	H2	H4	190	380	398	240	199		416		208					<table border="0"> <tr><td>H1</td><td>H3</td><td>H2</td><td>H4</td></tr> <tr><td>T1</td><td>H3</td><td>H2</td><td>H4</td></tr> <tr><td>X1</td><td>X2</td><td>X3</td><td>X4</td></tr> </table>	H1	H3	H2	H4	T1	H3	H2	H4	X1	X2	X3	X4	<p style="text-align: center;">hps</p> <p style="text-align: center;">CONTROL TRANSFORMER</p> <p style="text-align: center;">P/N C2G0250SP</p> <p style="text-align: center;">250 VA</p>	<p style="font-size: small;">252L E50394 PDG12 TYPE 3AH</p>	<p style="font-size: small;">LR3902 TYPE 3AH</p>	<table border="0"> <tr><td>P/N</td><td>C2G0250SP</td><td>LV TERMINAL LOCATION</td></tr> <tr><td></td><td>250 VA</td><td>1 2 3 1 1 2 3 1</td></tr> <tr><td></td><td>50/60 Hz</td><td>120 240</td></tr> <tr><td></td><td>130°C CLASS</td><td>115 230</td></tr> <tr><td></td><td></td><td>110 219</td></tr> <tr><td></td><td></td><td>X4 X2 X3 X1</td></tr> <tr><td></td><td></td><td>GND</td></tr> </table>	P/N	C2G0250SP	LV TERMINAL LOCATION		250 VA	1 2 3 1 1 2 3 1		50/60 Hz	120 240		130°C CLASS	115 230			110 219			X4 X2 X3 X1			GND
H1	H3	H2	H4																																																				
190	380	398	240																																																				
199		416																																																					
208																																																							
H1	H3	H2	H4																																																				
T1	H3	H2	H4																																																				
X1	X2	X3	X4																																																				
P/N	C2G0250SP	LV TERMINAL LOCATION																																																					
	250 VA	1 2 3 1 1 2 3 1																																																					
	50/60 Hz	120 240																																																					
	130°C CLASS	115 230																																																					
		110 219																																																					
		X4 X2 X3 X1																																																					
		GND																																																					

NOTES:



TITLE: 1 PHASE GENERAL PURPOSE CONTROL TFX

1	25/09/16	RH	UPDATED EDB	DES: MSARAF
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 1 OF 1

EDBC2G0250SP