



- FINGER GUARDS FOR TERMINAL BLOCKS AND FUSING OPTIONAL
- OPTIONAL FINGER GUARDS WILL ADD 0.1"[3mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WILL ADD 1.3"[33mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WITH FINGER GUARD WILL ADD 1.5"[38mm] TO HEIGHT
- TOLERANCES STD. +/- 0.1"[+/-3mm]
- ALL DIMENSIONS ARE IN INCHES [mm]

<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center;">H1 OV</td> <td style="text-align: center;">H2 208</td> <td style="text-align: center;">H3 277</td> <td style="text-align: center;">H4 380</td> </tr> <tr> <td style="text-align: center;">208</td> <td style="text-align: center;">277</td> <td style="text-align: center;">380</td> <td style="text-align: center;">380</td> </tr> <tr> <td style="text-align: center;">208</td> <td style="text-align: center;">277</td> <td style="text-align: center;">380</td> <td style="text-align: center;">380</td> </tr> </table> <p style="text-align: center;">HV TERMINAL LOCATION</p> <p style="text-align: center;"><b>hps</b></p> <p style="text-align: center;">MADE IN MEXICO SN</p>	H1 OV	H2 208	H3 277	H4 380	208	277	380	380	208	277	380	380		<p>LISTED 252L E50394 PDG12 TYPE PH</p> <p style="font-size: 2em; font-weight: bold;">hammond</p> <p>POWER SOLUTIONS</p> <p>CONTROL TRANSFORMER P/N C2M0750MGJ 750 VA</p>	<p>P/N C2M0750MGJ 750 VA 60/60 Hz 130°C CLASS</p>	<p>LISTED 252L E50394 PDG12 TYPE PH</p> <p>LV TERMINAL LOCATION</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center;">4</td> <td style="text-align: center;">2</td> <td style="text-align: center;">5</td> <td style="text-align: center;">1</td> <td style="text-align: center;">4</td> <td style="text-align: center;">2</td> <td style="text-align: center;">3</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="text-align: center;">120</td> <td style="text-align: center;">240</td> <td style="text-align: center;">120</td> <td style="text-align: center;">240</td> <td style="text-align: center;">120</td> <td style="text-align: center;">240</td> <td style="text-align: center;">120</td> <td style="text-align: center;">240</td> </tr> <tr> <td style="text-align: center;">X4</td> <td style="text-align: center;">X2</td> <td style="text-align: center;">X3</td> <td style="text-align: center;">X1</td> <td style="text-align: center;">GND</td> <td style="text-align: center;">GND</td> <td style="text-align: center;">GND</td> <td style="text-align: center;">GND</td> </tr> </table>	4	2	5	1	4	2	3	1	120	240	120	240	120	240	120	240	X4	X2	X3	X1	GND	GND	GND	GND
H1 OV	H2 208	H3 277	H4 380																																					
208	277	380	380																																					
208	277	380	380																																					
4	2	5	1	4	2	3	1																																	
120	240	120	240	120	240	120	240																																	
X4	X2	X3	X1	GND	GND	GND	GND																																	

NOTES:



TITLE: 1 PHASE MOLDED CONTROL TFX

1	25/09/16	RH	UPDATED EDB	DES: MSARAF
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 1 OF 1

EDBC2M0750MGJ