



- FINGER GUARDS FOR TERMINAL BLOCKS AND FUSING OPTIONAL
- OPTIONAL FUSE BLOCK FINGER GUARD WILL ADD 0.73"[19mm] TO WIDTH
- OPTIONAL FUSE BLOCK FINGER GUARD WILL ADD 0.2"[5mm] TO HEIGHT
- OPTIONAL TERMINAL BLOCK FINGER GUARD WILL ADD 0.38"[10mm] TO DEPTH
- TOLERANCES STD. +/- 0.1"[+/-3mm]
- ALL DIMENSIONS ARE IN INCHES [mm]
- ACCOUNT FOR REASONABLE SPACE FOR 240mm LONG FLEXIBLE WIRE AND CONNECTORS ON TERMINALS FROM TERMINALBLOCKS TO FUSEBLOCKS

<table border="0"> <tr><td>H1</td><td>H2</td><td>H3</td><td>H4</td></tr> <tr><td>OV</td><td>217</td><td>240</td><td>480</td></tr> <tr><td></td><td>208</td><td>230</td><td>460</td></tr> <tr><td></td><td>199</td><td>220</td><td>440</td></tr> </table> <p>HV TERMINAL LOCATION MADE IN MEXICO SN</p>	H1	H2	H3	H4	OV	217	240	480		208	230	460		199	220	440		<table border="0"> <tr><td>X3</td><td>X2</td><td>X1</td><td>GND</td></tr> </table>	X3	X2	X1	GND	<table border="0"> <tr><td>H1</td><td>H2</td><td>H3</td><td>H4</td></tr> </table> <p>CONTROL TRANSFORMER P/N C2M0050MLI-1 50 VA TYPE PH</p>	H1	H2	H3	H4	<p>LISTED 252L E50394 FD012</p>	<table border="0"> <tr><td>X3</td><td>X2</td><td>X1</td><td>GND</td></tr> </table>	X3	X2	X1	GND	<table border="0"> <tr><td>P/N</td><td>C2M0050MLI-1</td></tr> <tr><td>50 VA</td><td></td></tr> <tr><td>50/60 Hz</td><td></td></tr> <tr><td>130°C CLASS</td><td></td></tr> </table> <p>LISTED 252L E50394 TYPE PH</p>	P/N	C2M0050MLI-1	50 VA		50/60 Hz		130°C CLASS		<table border="0"> <tr><td>LV TERMINAL LOCATION</td><td></td><td></td></tr> <tr><td>120</td><td>25</td><td>OV</td></tr> <tr><td>115</td><td>24</td><td></td></tr> <tr><td>110</td><td>23</td><td></td></tr> <tr><td>X3</td><td>X2</td><td>X1</td></tr> <tr><td></td><td></td><td>GND</td></tr> </table>	LV TERMINAL LOCATION			120	25	OV	115	24		110	23		X3	X2	X1			GND
H1	H2	H3	H4																																																										
OV	217	240	480																																																										
	208	230	460																																																										
	199	220	440																																																										
X3	X2	X1	GND																																																										
H1	H2	H3	H4																																																										
X3	X2	X1	GND																																																										
P/N	C2M0050MLI-1																																																												
50 VA																																																													
50/60 Hz																																																													
130°C CLASS																																																													
LV TERMINAL LOCATION																																																													
120	25	OV																																																											
115	24																																																												
110	23																																																												
X3	X2	X1																																																											
		GND																																																											

NOTES:



TITLE: 1 PHASE MOLDED CONTROL TFX

NO.	DATE	BY	REVISION	DES: RHARISH	DATE: 25/10/22
				SCALE: NTS	

SHEET 1 OF 1

EDBC2M0050MLI-1