



- FINGER GUARDS FOR TERMINAL BLOCKS AND FUSING OPTIONAL
- OPTIONAL FUSE BLOCK FINGER GUARD WILL ADD 0.2" [5mm] TO HEIGHT
- OPTIONAL TERMINAL BLOCK FINGER GUARD WILL ADD 0.38" [10mm] TO DEPTH
- TOLERANCES STD. +/- 0.1" [+/-3mm]
- ALL DIMENSIONS ARE IN INCHES [mm]
- ACCOUNT FOR REASONABLE SPACE FOR 240mm LONG FLEXIBLE WIRE AND CONNECTORS ON TERMINALS FROM TERMINAL BLOCKS TO FUSE BLOCKS

	H1 H3 H2 H4 220 440 230 460 240 480 HV TERMINAL LOCATION 	 hammond POWER SOLUTIONS CONTROL TRANSFORMER P/NC2M1500MQMJ-1 1500 VA 	 LV TERMINAL LOCATION 120 240 115 230 110 220 X4 X2 X3 X1 GND	P/N C2M1500MQMJ-1 1500 VA 50/60 Hz 130°C CLASS
	MADE IN MEXICO SN			

NOTES:



TITLE: 1 PHASE MOLDED CONTROL TFX

				DES: RHARISH
				DATE: 25/10/22
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 1 OF 1

EDBC2M1500MQMJ-1

0.1 rharish 2025/10/22 15:11

THIS DRAWING CONTAINS STRICTLY CONFIDENTIAL INFORMATION BELONGING TO HAMMOND POWER SOLUTIONS AND MUST NOT BE DISTRIBUTED OUTSIDE AUTHORIZED PARTIES.