



- FINGER GUARDS FOR TERMINAL BLOCKS AND FUSING OPTIONAL
- OPTIONAL FINGER GUARDS WILL ADD 0.1"[3mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WILL ADD 1.3"[33mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WITH FINGER GUARD WILL ADD 1.5"[38mm] TO HEIGHT
- TOLERANCES STD. +/- 0.1"[+/-3mm]
- ALL DIMENSIONS ARE IN INCHES [mm]

<table border="0"> <tr><td>H1</td><td>H3</td><td>H2</td><td>H4</td></tr> <tr><td>220</td><td>440</td><td>460</td><td>480</td></tr> <tr><td>230</td><td></td><td>460</td><td>480</td></tr> <tr><td>240</td><td></td><td></td><td></td></tr> </table>	H1	H3	H2	H4	220	440	460	480	230		460	480	240							<table border="0"> <tr><td>H1</td><td>H3</td><td>H2</td><td>H4</td></tr> <tr><td colspan="4">CONTROL TRANSFORMER</td></tr> <tr><td colspan="4">P/N C2M0500QR</td></tr> <tr><td colspan="4">500 VA</td></tr> <tr><td colspan="4">LISTED 252L</td></tr> <tr><td colspan="4">E50394</td></tr> <tr><td colspan="4">PDG12</td></tr> </table>	H1	H3	H2	H4	CONTROL TRANSFORMER				P/N C2M0500QR				500 VA				LISTED 252L				E50394				PDG12						<table border="0"> <tr><td>P/N</td><td>LV TERMINAL LOCATION</td></tr> <tr><td>C2M0500QR</td><td>24</td></tr> <tr><td>500 VA</td><td>23</td></tr> <tr><td>50/60 Hz</td><td>22</td></tr> <tr><td>130°C CLASS</td><td>X2</td></tr> <tr><td></td><td>OV</td></tr> <tr><td></td><td>X1</td></tr> <tr><td></td><td>GND</td></tr> </table>	P/N	LV TERMINAL LOCATION	C2M0500QR	24	500 VA	23	50/60 Hz	22	130°C CLASS	X2		OV		X1		GND
H1	H3	H2	H4																																																																
220	440	460	480																																																																
230		460	480																																																																
240																																																																			
H1	H3	H2	H4																																																																
CONTROL TRANSFORMER																																																																			
P/N C2M0500QR																																																																			
500 VA																																																																			
LISTED 252L																																																																			
E50394																																																																			
PDG12																																																																			
P/N	LV TERMINAL LOCATION																																																																		
C2M0500QR	24																																																																		
500 VA	23																																																																		
50/60 Hz	22																																																																		
130°C CLASS	X2																																																																		
	OV																																																																		
	X1																																																																		
	GND																																																																		

NOTES:



TITLE: 1 PHASE MOLDED CONTROL TFX

			DES: MSARAF
			DATE: 25/06/30
NO.	DATE	BY	REVISION
			SCALE: NTS

SHEET 1 OF 1

EDBC2M0500QR