



- FINGER GUARDS FOR TERMINAL BLOCKS AND FUSING OPTIONAL
- OPTIONAL FINGER GUARDS WILL ADD 0.1"[3mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WILL ADD 1.3"[33mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WITH FINGER GUARD WILL ADD 1.5"[38mm] TO HEIGHT
- TOLERANCES STD. +/- 0.1"[+/-3mm]
- ALL DIMENSIONS ARE IN INCHES [mm]

<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">H1 190</td> <td style="width: 25%;">H3 380</td> <td style="width: 25%;">H2 398</td> <td style="width: 25%;">H4 416</td> </tr> <tr> <td>1 3</td> <td>2 4</td> <td>1 3</td> <td>2 4</td> </tr> </table> <p>HV TERMINAL LOCATION</p> <p>hps</p> <p>MADE IN MEXICO SN</p>	H1 190	H3 380	H2 398	H4 416	1 3	2 4	1 3	2 4		<p>LISTED 252L E50394 PDG12 TYPE PH</p> <p>hammond POWER SOLUTIONS</p> <p>CONTROL TRANSFORMER P/N C2M0750SP 750 VA</p>	<p>P/N C2M0750SP 750 VA 50/60 Hz 130°C CLASS</p>	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">LV TERMINAL LOCATION</td> <td style="width: 25%;">120</td> <td style="width: 25%;">240</td> <td style="width: 25%;">4 2 3 1</td> </tr> <tr> <td></td> <td>115</td> <td>230</td> <td></td> </tr> <tr> <td></td> <td>110</td> <td>219</td> <td></td> </tr> <tr> <td></td> <td>X4</td> <td>X2</td> <td>X3 X1 GND</td> </tr> </table>	LV TERMINAL LOCATION	120	240	4 2 3 1		115	230			110	219			X4	X2	X3 X1 GND
H1 190	H3 380	H2 398	H4 416																									
1 3	2 4	1 3	2 4																									
LV TERMINAL LOCATION	120	240	4 2 3 1																									
	115	230																										
	110	219																										
	X4	X2	X3 X1 GND																									

NOTES:



TITLE: 1 PHASE MOLDED CONTROL TFX

1	25/09/16	RH	UPDATED EDB	DES: MSARAF
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 1 OF 1

EDBC2M0750SP