



- FINGER GUARDS FOR TERMINAL BLOCKS AND FUSING OPTIONAL
- OPTIONAL FINGER GUARDS WILL ADD 0.1[3mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WILL ADD 1.3"[33mm] TO HEIGHT
- OPTIONAL FUSE BLOCK WITH FINGER GUARD WILL ADD 1.5"[38mm] TO HEIGHT
- TOLERANCES STD. +/- 0.1"[+/-3mm]
- ALL DIMENSIONS ARE IN INCHES [mm]

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>H1</td><td>H2</td><td>H3</td><td>H4</td><td>H5</td></tr> <tr> <td>0V</td><td>240</td><td>415</td><td>480</td><td>600</td></tr> <tr> <td></td><td>230</td><td>398</td><td>460</td><td>575</td></tr> <tr> <td></td><td>220</td><td>380</td><td>440</td><td>550</td></tr> </table> <p>HV TERMINAL LOCATION</p> <p><b>hps</b></p> <p>MADE IN MEXICO SN</p>	H1	H2	H3	H4	H5	0V	240	415	480	600		230	398	460	575		220	380	440	550		<p>LISTED 252L E50394 180-7 TYPE PH</p> <p><b>CE</b></p>	<p><b>hammond</b></p> <p>POWER SOLUTIONS</p> <p>CONTROL TRANSFORMER P/N C2M0500XI 500 VA</p> <p>H1 H2 H3 H4 H5</p> <p>T2 T1 X3 X2 X1 GND</p>	<p>P/N C2M0500XI 500 VA 50/60 Hz 180°C CLASS</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td></td><td></td><td></td><td></td><td></td></tr> <tr> <td></td><td></td><td></td><td></td><td></td></tr> <tr> <td></td><td></td><td></td><td></td><td></td></tr> <tr> <td></td><td></td><td></td><td></td><td></td></tr> <tr> <td></td><td></td><td></td><td></td><td></td></tr> </table> <p>LV TERMINAL LOCATION</p> <p><b>UL</b> LISTED E50394 180-7 TYPE PH</p> <p><b>CE</b></p>																									
H1	H2	H3	H4	H5																																														
0V	240	415	480	600																																														
	230	398	460	575																																														
	220	380	440	550																																														

NOTES:



TITLE: 1 PHASE MOLDED CONTROL TFX

1	25/09/16	RH	UPDATED EDB	DES: MSARAF
NO.	DATE	BY	REVISION	SCALE: NTS

SHEET 1 OF 1

EDBC2M0500XI