

# PRODUCT DATA SHEET

Open Style Control Transformer

Cat. Number: C2G0750XMH

Rating: 750VA  
 Phase: 1  
 Freq: 50/60 Hz  
 Temp. Rise: 80°C  
 Enclosure: Core & Coil  
 Material: Copper  
 Ins. Class: 130°C

| DIMENSIONS |     |       |
|------------|-----|-------|
|            | in  | mm    |
| Height     | 4.8 | 121   |
| Width      | 5.3 | 133.4 |
| Depth      | 6.5 | 166.1 |

|        | lbs  | kg  |
|--------|------|-----|
| Weight | 20.6 | 9.3 |

| PRIMARY     |                 | SECONDARY   |                |
|-------------|-----------------|-------------|----------------|
| Voltage     | 230/400/460/575 | Voltage     | 95/115         |
| Connection  | Series (V)      | Connection  | Series (V)     |
| Termination | Terminal Block  | Termination | Terminal Block |

|                                    |                            |
|------------------------------------|----------------------------|
| Load Inrush VA at 40% Power Factor | 5% Voltage Drop @ 1720 VA  |
|                                    | 10% Voltage Drop @ 2885 VA |
|                                    | 15% Voltage Drop @ 4000 VA |
| Full Load Watts Loss               | 69.5 Watts                 |

|                   |                         |
|-------------------|-------------------------|
| Country of Origin | Mexico                  |
| Certifications    | CSA: LR3902, UL: E50394 |