

PRODUCT DATA SHEET

Molded Style Control Transformer

Cat. Number: C2M1500AJ

Rating: 1.5KVA
 Phase: 1
 Freq: 60 Hz
 Temp. Rise: 80°C
 Enclosure: Core & Coil
 Material: Copper
 Ins. Class: 130°C

| DIMENSIONS | | |
|------------|-----|---------|
| | in | mm |
| Height | 5.7 | 144.8 |
| Width | 6.4 | 161.925 |
| Depth | 7.4 | 188.3 |

| | lbs | kg |
|--------|------|------|
| Weight | 32.1 | 14.6 |

| PRIMARY | | SECONDARY | |
|-------------|----------------|-------------|--------------------------|
| Voltage | 600 | Voltage | 120X240 |
| Connection | Series (V) | Connection | Parallel x Series (Vx2V) |
| Termination | Terminal Block | Termination | Terminal Block |

| | |
|------------------------------------|-----------------------------|
| Load Inrush VA at 40% Power Factor | 5% Voltage Drop @ 6225 VA |
| | 10% Voltage Drop @ 11015 VA |
| | 15% Voltage Drop @ 15600 VA |
| Full Load Watts Loss | 87.6 Watts |

| | |
|-------------------|------------|
| Country of Origin | Mexico |
| Certifications | UL: E50394 |