

# PRODUCT DATA SHEET

Molded Style Control Transformer

Cat. Number: C2M0750MQMJ-1

Rating: 750VA  
 Phase: 1  
 Freq: 50/60 Hz  
 Temp. Rise: 80°C  
 Enclosure: Core & Coil  
 Material: Copper  
 Ins. Class: 130°C

| DIMENSIONS |     |        |
|------------|-----|--------|
|            | in  | mm     |
| Height     | 6.1 | 121    |
| Width      | 5.3 | 133.35 |
| Depth      | 6.2 | 157.1  |

|        | lbs  | kg  |
|--------|------|-----|
| Weight | 17.0 | 7.7 |

| PRIMARY     |                          | SECONDARY   |                          |
|-------------|--------------------------|-------------|--------------------------|
| Voltage     | 240x480                  | Voltage     | 120x240                  |
| Connection  | Parallel x Series (Vx2V) | Connection  | Parallel x Series (Vx2V) |
| Termination | Terminal Block           | Termination | Terminal Block           |

|                                    |                            |
|------------------------------------|----------------------------|
| Load Inrush VA at 40% Power Factor | 5% Voltage Drop @ 1865 VA  |
|                                    | 10% Voltage Drop @ 3465 VA |
|                                    | 15% Voltage Drop @ 4970 VA |
| Full Load Watts Loss               | 54.5 Watts                 |

|                   |            |
|-------------------|------------|
| Country of Origin | Mexico     |
| Certifications    | UL: E50394 |