

PRODUCT DATA SHEET

Molded Style Control Transformer

Cat. Number: C2M0750PP

Rating: 750VA
 Phase: 1
 Freq: 50/60 Hz
 Temp. Rise: 80°C
 Enclosure: Core & Coil
 Material: Copper
 Ins. Class: 130°C

| DIMENSIONS | | |
|------------|-----|--------|
| | in | mm |
| Height | 4.8 | 121 |
| Width | 5.3 | 133.35 |
| Depth | 6.2 | 157.1 |

| | lbs | kg |
|--------|------|-----|
| Weight | 17.0 | 7.7 |

| PRIMARY | | SECONDARY | |
|-------------|--------------------------|-------------|--------------------------|
| Voltage | 120X240 | Voltage | 120x240 |
| Connection | Parallel x Series (Vx2V) | Connection | Parallel x Series (Vx2V) |
| Termination | Terminal Block | Termination | Terminal Block |

| | |
|------------------------------------|----------------------------|
| Load Inrush VA at 40% Power Factor | 5% Voltage Drop @ 1970 VA |
| | 10% Voltage Drop @ 3545 VA |
| | 15% Voltage Drop @ 5025 VA |
| Full Load Watts Loss | 54.8 Watts |

| | |
|-------------------|------------|
| Country of Origin | Mexico |
| Certifications | UL: E50394 |