

PRODUCT DATA SHEET

Molded Style Control Transformer

Cat. Number: C2M0100XI

Rating: 100VA
 Phase: 1
 Freq: 50/60 Hz
 Temp. Rise: 80°C
 Enclosure: Core & Coil
 Material: Copper
 Ins. Class: 130°C

| DIMENSIONS | | |
|------------|-----|-------|
| | in | mm |
| Height | 3.7 | 94.1 |
| Width | 4.0 | 102 |
| Depth | 4.0 | 100.7 |

| | lbs | kg |
|--------|-----|-----|
| Weight | 4.0 | 1.8 |

| PRIMARY | | SECONDARY | |
|-------------|-----------------|-------------|----------------|
| Voltage | 230/400/460/575 | Voltage | 24/115 |
| Connection | Series (V) | Connection | Series (V) |
| Termination | Terminal Block | Termination | Terminal Block |

| | |
|------------------------------------|---------------------------|
| Load Inrush VA at 40% Power Factor | 5% Voltage Drop @ 200 VA |
| | 10% Voltage Drop @ 265 VA |
| | 15% Voltage Drop @ 320 VA |
| Full Load Watts Loss | 20.6 Watts |

| | |
|-------------------|------------|
| Country of Origin | Mexico |
| Certifications | UL: E50394 |