

# Push-in Y-connector NPQP-Y-Q10-Q8-FD-P10

Part number: 133126

FESTO



## Data sheet

| Feature                                       | Value                                                                   |
|-----------------------------------------------|-------------------------------------------------------------------------|
| Size                                          | Standard                                                                |
| Nominal size                                  | 6.5 mm                                                                  |
| Design                                        | Y-shape<br>Push-pull principle                                          |
| Size of pack                                  | 10                                                                      |
| Operating pressure complete temperature range | -0.095 MPa...0.45 MPa<br>-0.95 bar...4.5 bar<br>-13.775 psi...65.25 psi |
| Temperature-dependent operating pressure      | -0.095 MPa...1 MPa<br>-0.95 bar...10 bar<br>-13.775 psi...145 psi       |
| Operating medium                              | Compressed air to ISO 8573-1:2010 [7:-:-]                               |
| Note on operating and pilot medium            | Lubricated operation possible                                           |
| Corrosion resistance class CRC                | 4 - Very high corrosion stress                                          |
| LABS (PWIS) conformity                        | VDMA24364 zone III                                                      |
| Suitable for use with food                    | See supplementary material information                                  |
| Ambient temperature                           | -20 °C...60 °C                                                          |
| Product weight                                | 16 g                                                                    |
| Pneumatic connection, port 1                  | For tubing outer diameter of 10 mm                                      |
| Pneumatic connection, port 2                  | For tubing outside diameter of 8 mm                                     |
| Colour of release ring                        | Transparent white                                                       |
| Note on materials                             | RoHS-compliant                                                          |
| Material housing                              | PP                                                                      |
| Material tubing clamp component               | High-alloy stainless steel                                              |