


# ISO cylinder DSBG-80-500-PPVA-N3

Part number: 1646782

FESTO



## Data sheet

| Feature  | Value  |
|--|--|
| Stroke   | 500 mm   |
| Piston diameter  | 80 mm  |
| Piston rod thread  | M20x1.5  |
| Cushioning   | Pneumatic cushioning, adjustable at both ends  |
| Mounting position  | optional   |
| Conforms to standard   | ISO 15552  |
| Piston-rod end   | Male thread  |
| Design   | Piston<br>Piston rod<br>Tie rod<br>Cylinder barrel   |
| Position detection   | Via proximity switch   |
| Variants   | Piston rod at one end  |
| Operating pressure   | 0.04 MPa...1.2 MPa<br>0.4 bar...12 bar   |
| Mode of operation  | Double-acting  |
| Operating medium   | Compressed air to ISO 8573-1:2010 [7:4:4]  |
| Note on operating and pilot medium                           | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC                               | 2 - Moderate corrosion stress  |
| LABS (PWIS) conformity                                       | VDMA24364-B1/B2-L  |
| Ambient temperature  | -20 °C...80 °C   |
| Impact energy in end positions                               | 1.8 J  |
| Cushioning length  | 31 mm  |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke  | 2721 N   |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 3016 N   |
| Moving mass  | 2760 g   |
| Moving mass for 0 mm stroke                                  | 810 g  |
| Additional moving mass per 10 mm stroke                      | 39 g   |
| Product weight   | 6910 g   |
| Basic weight for 0 mm stroke                                 | 2660 g   |
| Additional weight per 10 mm stroke                           | 85 g   |

| Feature                     | Value  |
|-----------------------------|--|
| Type of mounting            | Either:<br>Via female thread<br>With accessories |
| Pneumatic connection        | G3/8   |
| Note on materials           | RoHS-compliant                                   |
| Material cover              | Coated die-cast aluminium                        |
| Material piston seal        | TPE-U(PU)  |
| Material piston             | Wrought aluminium alloy                          |
| Material piston rod         | High-alloy steel                                 |
| Material piston rod wiper   | TPE-U(PU)  |
| Buffer seal material        | TPE-U(PU)  |
| Material of cushioning boss | POM  |
| Material cylinder barrel    | Smooth-anodised wrought aluminium alloy          |
| Material nut                | Galvanised steel                                 |
| Material bearing            | POM  |
| Material collar nut         | Galvanised steel                                 |
| Material tie rod            | High-alloy steel                                 |