

Ball valve VZBA-3"-WW-63-T-22-F0710-V4V4T

Part number: 1686704

FESTO



Data sheet

| Feature | Value |
|------------------------------|--|
| Design | 2-way ball valve |
| Type of actuation | Mechanical |
| Sealing principle | Soft |
| Mounting position | optional |
| Type of mounting | In-line installation |
| Connection Process valve | Weld-on ends/weld-on ends |
| Switching position indicator | Slot direction = flow direction |
| Flange hole pattern | F07 F10 |
| Inside diameter | 80 mm |
| Nominal size DN | 80 |
| Valve function | 2/2 |
| Manual override | None |
| Flow direction | Reversible |
| Nominal pressure PN | 63 |
| Actuating torque | 112 Nm |
| Based on standard | DIN 3202-S13 ISO 5211 |
| Medium | Compressed air to ISO 8573-1:2010 [:-:-] Inert gases Water – no water vapour Neutral fluids Other media on request |
| Media temperature | -10 °C...200 °C |
| Flow rate Kv | 905 m ³ /h |
| Note on materials | RoHS-compliant |
| LABS (PWIS) conformity | VDMA24364 zone III |

| Feature | Value |
|--|--|
| Material housing | High-alloy stainless steel |
| Material number housing | 1.4408 |
| Material seals | FPM PTFE PTFE reinforced |
| Material ball | High-alloy stainless steel |
| Material number ball | 1.4408 |
| Material shaft | High-alloy stainless steel |
| Material number shaft | 1.4401 |
| Product weight | 13950 g |
| CE mark (see declaration of conformity) | In accordance with EU Pressure Equipment Directive |
| UKCA marking (see declaration of conformity) | to UK Pressure Equipment Regulations |
| Explosion protection | Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX) |
| Corrosion resistance class CRC | 3 - high corrosion stress |