

# Service unit combination
# FRC-1/4-D-MIDI-KF-A

Part number: 185844





## Data sheet

| Feature | Value |
|---|---|
| Size | Midi |
| Series | D |
| Actuator lock | Rotary knob with detent |
| Mounting position | Vertical +/-5° |
| Grade of filtration | 40 µm |
| Condensate drain | Fully automatic |
| Design | Branching module<br>Pressure switch<br>On/off valve<br>Filter regulator with pressure gauge<br>Proportional standard mist lubricator<br>Safety start-up valve |
| Max. condensate volume | 43 cm³ |
| Bowl guard | Metal bowl guard |
| Pressure gauge (ANALOG) or Pressure display (DIGITAL) | With pressure gauge |
| Operating pressure | 0.3 MPa...1.2 MPa<br>3 bar...12 bar<br>43.5 psi...174 psi |
| Pressure regulation range | 0.25 MPa...1.2 MPa<br>2.5 bar...12 bar<br>36.25 psi...174 psi |
| Max. pressure hysteresis | 0.025 MPa<br>0.25 bar<br>3.625 psi |
| Standard nominal flow rate (standardised to DIN 1343) | 1060 l/min |
| Operating medium | Compressed air to ISO 8573-1:2010 [-:-:-]<br>Inert gases |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Air purity class at output | Compressed air to ISO 8573-1:2010 [7:4:-]<br>Inert gases |
| Media temperature | -10 °C...60 °C |
| Ambient temperature | -10 °C...60 °C |
| Product weight | 4000 g |

| Feature | Value |
|---|---|
| Type of mounting | Either:<br>In-line installation<br>With accessories |
| Pneumatic connection, port 1 | G1/4 |
| Pneumatic connection, port 2 | G1/4 |
| Material housing | Die-cast zinc |
| Material bowl | PC |