

# Multiple distributor QSLV3-3/8-1/2-U

Part number: 190786

FESTO



## Data sheet

| Feature                                       | Value                                                             |
|-----------------------------------------------|-------------------------------------------------------------------|
| Size                                          | Standard                                                          |
| Nominal size                                  | 6.8 mm                                                            |
| Type of seal on screwed plug                  | Coating                                                           |
| Mounting position                             | optional                                                          |
| Design                                        | Push-pull principle                                               |
| Size of pack                                  | 1                                                                 |
| Operating pressure complete temperature range | -0.095 MPa...1 MPa<br>-0.95 bar...10 bar<br>-13.775 psi...145 psi |
| Maritime classification                       | See certificate                                                   |
| Operating medium                              | Compressed air to ISO 8573-1:2010 [7:-:-]                         |
| Note on operating and pilot medium            | Lubricated operation possible                                     |
| Corrosion resistance class CRC                | 1 - Low corrosion stress                                          |
| LABS (PWIS) conformity                        | VDMA24364-B1/B2-L                                                 |
| Ambient temperature                           | -10 °C...60 °C<br>14 °F...140 °F                                  |
| Max. tightening torque                        | 24 Nm                                                             |
| Product weight                                | 170 g                                                             |
| Number of outputs                             | 3                                                                 |
| Number of supply lines                        | 1                                                                 |
| Pneumatic connection, port 1                  | Male thread 3/8 NPT                                               |
| Pneumatic connection, port 2                  | For tubing outside diameter of 1/2"                               |
| Colour of release ring                        | grey                                                              |
| Material screwed plug                         | Nickel-plated brass                                               |
| Note on materials                             | RoHS-compliant                                                    |
| Material housing                              | PBT                                                               |
| Material release ring                         | POM                                                               |
| Material tubing seal                          | NBR                                                               |
| Material tubing clamp component               | High-alloy stainless steel                                        |