

# ISO cylinder DSBG-200-200-P-N3

Part number: 2537456

**FESTO**



## Data sheet

| Feature  | Value  |
|--|--|
| Stroke   | 200 mm   |
| Piston diameter  | 200 mm   |
| Piston rod thread  | M36x2  |
| Cushioning   | Elastic cushioning rings/plates at both ends   |
| Mounting position  | optional   |
| Conforms to standard   | ISO 15552  |
| Piston-rod end   | Male thread  |
| Design   | Piston<br>Piston rod<br>Tie rod<br>Cylinder barrel   |
| Variants   | Piston rod at one end  |
| Operating pressure   | 0.06 MPa...1 MPa<br>0.6 bar...10 bar   |
| Mode of operation  | Double-acting  |
| Operating medium   | Compressed air to ISO 8573-1:2010 [7:4:4]  |
| Note on operating and pilot medium                           | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC                               | 2 - Moderate corrosion stress  |
| LABS (PWIS) conformity                                       | VDMA24364-B1/B2-L  |
| Ambient temperature  | -20 °C...80 °C   |
| Impact energy in end positions                               | 4.8 J  |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke  | 18096 N  |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 18850 N  |
| Moving mass  | 7288 g   |
| Moving mass for 0 mm stroke                                  | 5348 g   |
| Additional moving mass per 10 mm stroke                      | 97 g   |
| Product weight   | 20413 g  |
| Basic weight for 0 mm stroke                                 | 15493 g  |
| Additional weight per 10 mm stroke                           | 246 g  |
| Type of mounting   | Either:<br>Via female thread<br>With accessories   |

| <b>Feature</b>              | <b>Value</b>                            |
|-----------------------------|---|
| Pneumatic connection        | G3/4                                    |
| Note on materials           | RoHS-compliant                          |
| Material cover              | Cast aluminium, coated                  |
| Material piston seal        | NBR                                     |
| Material piston             | Cast aluminium                          |
| Material piston rod         | High-alloy steel                        |
| Material piston rod wiper   | NBR                                     |
| Buffer seal material        | TPE-U(PU)                               |
| Material of cushioning boss | POM                                     |
| Material cylinder barrel    | Smooth-anodised wrought aluminium alloy |
| Material nut                | Galvanised steel                        |
| Material bearing            | Metal polymer compound                  |
| Material collar nut         | Galvanised steel                        |
| Material tie rod            | High-alloy steel                        |